

DISCRIPTION

TOP BOAT LIFE is a high-performance two-stroke engine oil specially formulated for modern water-cooled outboard engines. It provides excellent lubrication, superior engine cleanliness, and reliable protection against corrosion and wear in both freshwater and saltwater marine environments.

TOP BOAT LIFE is a premium quality ashless two-stroke lubricant designed to meet the performance requirements of modern high-speed outboard engines operating in marine environments. It is formulated with high-quality base oils and advanced additive technology to ensure excellent lubrication, reduced piston deposits, and superior engine protection.

This oil provides excellent resistance to rust and corrosion caused by moisture and saltwater exposure, ensuring long engine life and reliable operation. The ashless detergent system helps minimize spark plug fouling and reduces exhaust smoke while maintaining clean combustion chambers and piston rings.

APPLICATION

TOP BOAT LIFE is recommended for use in

- Water-cooled two-stroke outboard engines
- Marine outboard engines operating in freshwater or saltwater
- Personal watercraft and jet skis
- Small marine two-stroke engines requiring NMMA TC-W3 performance level
- Engines equipped with premix or automatic oil injection systems

BENEFITS

- Excellent protection against engine wear and scuffing
- Superior resistance to rust and corrosion in marine environments
- Ashless formulation helps reduce deposits and spark plug fouling
- Provides cleaner combustion and reduced exhaust smoke
- Maintains piston cleanliness and prevents ring sticking
- Suitable for premix and oil injection systems
- Ensures reliable performance in high-speed marine engines

PRODUCT DATA SHEET



Performance

NMMA TC-W3

Packaging: 1Q,1L,4Q, 4L,5Q, 5L, 18L, 20L, 25L, Drums, IBC.

Specification

| Test Parameter | Units | Test Limits | Test Method |
|-----------------------|-------------------|-------------------|--------------|
| Appearance | - | Clear Blue Liquid | Visual |
| Density @ 15°C | g/cm ³ | 0.866 | ASTM D-4052 |
| Viscosity @ 40°C | cSt | 45 – 60 | ASTM D-445 |
| Viscosity @ 100°C | cSt | 7 – 9 | ASTM D-445 |
| Viscosity Index, min. | - | 130 | ASTM D- 2270 |
| Flash Point min. | °C | 115 | ASTM D-92 |
| Pour Point, max. | °C | -22 | ASTM D-97 |
| Code | - | 200/1 | - |

TOP BOAT LIFE

TC-W3

FULLY SYNTHETIC