

DISCRIPTION

FULLY BOAT LIFE Fully Synthetic Marine Engine Oil is a premium high-performance lubricant formulated with advanced synthetic base oils and modern additive technology to provide excellent protection for marine engines. It offers superior resistance to wear, oxidation, and corrosion while ensuring reliable engine performance in both freshwater and saltwater environments.

FULLY BOAT LIFE is a high-quality fully synthetic lubricant designed to provide outstanding protection and performance for marine engines operating under demanding conditions. It is formulated using advanced synthetic base oils and a balanced additive system to deliver excellent oxidation stability, superior engine cleanliness, and enhanced protection against wear and deposits.

This oil provides excellent resistance to thermal breakdown and maintains strong oil film strength during continuous high-load and high-temperature operation commonly experienced in marine environments. Its advanced formulation also provides effective protection against rust and corrosion caused by moisture and saltwater exposure.

APPLICATION

FULLY BOAT LIFE is recommended for use in

- High-performance marine gasoline engines
- Marine engines operating in freshwater or saltwater environments
- Four-stroke marine engines requiring high-performance synthetic engine oil
- Turbocharged and high-output marine engines
- Marine equipment operating under severe load and continuous operation

BENEFITS

- Excellent protection against engine wear and scuffing
- Superior resistance to oxidation and thermal breakdown
- Outstanding protection against rust and corrosion in marine environments
- Helps maintain engine cleanliness and reduce sludge formation
- Provides strong lubrication film under high-load operating conditions
- Ensures reliable engine performance at high operating temperatures
- Supports extended engine life and improved engine reliability

PRODUCT DATA SHEET



Performance

ACEA A3/B3

AVAILABILITY

ISO VG Grade 68, 100, 150, 220, 320, 460 and 680

Packaging: 1Q,1L,4Q, 4L,5Q, 5L, 18L, 20L, 25L, Drums, IBC.

Specification

Test Parameter	Units	Test Limits	Test Method
SAE Grade	-	5W40	-
Appearance	-	C&B	Visual
Density @ 15°C	g/cm ³	0.863	ASTM D-4052
Viscosity @ 40°C	cSt	92	ASTM D-445
Viscosity @ 100°C	cSt	12.5– 16.2	ASTM D-445
Viscosity Index, min.	-	135	ASTM D- 2270
Flash Point min.	°C	220	ASTM D-92
Pour Point, max.	°C	-28	ASTM D-97
TBN, min	mg/g	6	ASTM D-2896
Code	-	203/7	-