

DISCRIPTION

TOP BOAT LIFE PLUS is a high-performance lubricant formulated with advanced synthetic technology base oils and modern additive systems to provide excellent protection for marine engines. It delivers superior resistance to wear, oxidation, and corrosion while ensuring reliable engine performance in both freshwater and saltwater environments.

TOP BOAT LIFE PLUS is a premium quality lubricant specially designed for marine engines operating under demanding conditions. It is formulated with synthetic technology base oils and a balanced additive system to provide excellent oxidation stability, strong oil film strength, and superior protection against engine wear and deposits.

This oil offers outstanding resistance to thermal breakdown and maintains effective lubrication during continuous high-load and high-temperature operation typical of marine engines. Its advanced formulation also provides excellent protection against rust and corrosion caused by moisture and saltwater exposure.

APPLICATION

TOP BOAT LIFE PLUS is recommended for use in

- High-performance marine gasoline engines
- Four-stroke marine engines operating under heavy load conditions
- Marine engines used in both freshwater and saltwater environments
- Turbocharged and high-output marine engines
- Marine equipment requiring high-performance synthetic technology engine oil

BENEFITS

- Excellent protection against engine wear and scuffing
- Superior resistance to oxidation and thermal degradation
- Outstanding protection against rust and corrosion in marine environments
- Helps maintain engine cleanliness and reduce sludge formation
- Provides strong lubrication film under high-load operating conditions
- Ensures reliable engine performance at high operating temperatures
- Helps extend engine life and improve engine reliability

PRODUCT DATA SHEET



Performance

ACEA A3/B3

AVAILABILITY

SAE Grades 5W40

Packaging: 1Q,1L,4Q, 4L,5Q, 5L, 18L, 20L, 25L, Drums, IBC.

Specification

Test Parameter	Units	Test Limits	Test Method
SAE Grade	-	5W40	-
Appearance	-	C&B	Visual
Density @ 15°C	g/cm ³	0.863	ASTM D-4052
Viscosity @ 40°C	cSt	92	ASTM D-445
Viscosity @ 100°C	cSt	12.5– 16.2	ASTM D-445
Viscosity Index, min.	-	135	ASTM D- 2270
Flash Point min.	°C	220	ASTM D-92
Pour Point, max.	°C	-28	ASTM D-97
TBN, min	mg/g	6	ASTM D-2896
Code	-	204/7	-