

DISCRIPTION

TECHNO BIKE LIFE is a high-quality lubricant specially formulated for four-stroke motorcycles. It provides excellent engine protection, smooth clutch performance, and reliable lubrication under a wide range of operating conditions.

TECHNO BIKE LIFE is formulated with high-quality base oils and advanced additive technology to provide superior protection and performance for modern four-stroke motorcycle engines. The formulation ensures excellent engine cleanliness, improved wear protection, and stable viscosity performance even under high-temperature and high-speed operating conditions.

This oil is designed to deliver reliable lubrication for engine, gearbox, and wet clutch systems commonly found in motorcycles. It helps reduce engine deposits, prevents oxidation and sludge formation, and provides smooth clutch engagement for improved riding performance.

APPLICATION

TECHNO BIKE LIFE is recommended for use in

- Modern four-stroke motorcycles and scooters
- Air-cooled and water-cooled motorcycle engines
- Motorcycles with integrated gearbox and wet clutch systems
- High-performance motorcycles operating under severe conditions
- Engines requiring API SL and JASO MA / MA2 performance levels

BENEFITS

- Excellent protection against engine wear and scuffing
- Smooth wet clutch performance and improved gear shifting
- Superior engine cleanliness and deposit control
- High thermal and oxidation stability
- Helps prevent sludge and varnish formation
- Reliable lubrication under high-speed and high-temperature conditions
- Protects engine components from rust and corrosion
- Extends engine service life

PRODUCT DATA SHEET



Performance

- API SL
- JASO MA / MA2

AVAILABILITY

SAE Grades 5W40, 10W30, 10W40, 15W40, 20W40, 15W50 and 20W50.

Packaging: 1Q, 1L, 4Q, 4L, 5Q, 5L, 18L, 20L, 25L, Drums, IBC.

Specification

Test Parameter	Units	Test Limits	Test Method
SAE Grade	-	20W40	-
Appearance	-	C&B	Visual
Density @ 15°C	g/cm ³	0.863	ASTM D-4052
Viscosity @ 40°C	cSt	92	ASTM D-445
Viscosity @ 100°C	cSt	12.5– 16.2	ASTM D-445
Viscosity Index, min.	-	135	ASTM D- 2270
Flash Point min.	°C	220	ASTM D-92
Pour Point, max.	°C	-22	ASTM D-97
TBN, min	mg/g	6	ASTM D-2896
Code	-	303/5	-

TECHNO BIKE LIFE
FULLY SYNTHETIC 20W40 SL/FWC (4T)