

## DISCRIPTION

**TOP BIKE LIFE** engine oil is a high-performance lubricant specially formulated for two-stroke motorcycle engines. It provides excellent lubrication, clean combustion, and effective protection against wear, deposits, and engine scuffing under high-temperature and high-speed operating conditions.

**TOP BIKE LIFE** is a premium quality lubricant designed for modern air-cooled and water-cooled two-stroke motorcycle engines. It is formulated with carefully selected base oils and advanced additive technology to deliver superior engine protection, reduced smoke formation, and improved combustion efficiency. This oil ensures excellent piston cleanliness, minimizes carbon deposits, and provides effective protection against wear, corrosion, and ring sticking. Its balanced formulation helps maintain engine performance, prolong engine life, and ensures smooth engine operation even under severe riding conditions.

## APPLICATION

**TOP BIKE LIFE** is recommended for use in

- Two-stroke motorcycles and scooters
- Air-cooled and water-cooled 2-stroke engines
- Oil injection systems and premix lubrication systems
- Mopeds, small motorcycles, and recreational bikes
- Other small two-stroke engines requiring API TC performance level

## BENEFITS

- Excellent engine protection against wear and scuffing
- Reduces piston deposits and exhaust port blockage
- Low smoke formulation for cleaner operation
- Improves combustion efficiency and engine performance
- Prevents spark plug fouling
- Excellent detergency and engine cleanliness
- Good mixing ability with fuel
- Helps extend engine life

## PRODUCT DATA SHEET



### Performance

- API TC
- JASO FB / FC
- ISO-L-EGB / ISO-L-EGC

**Packaging:** 1Q,1L,4Q, 4L,5Q, 5L, 18L, 20L, 25L, Drums, IBC.

### Specification

Test Parameter	Units	Test Limits	Test Method
Appearance	-	Clear & Bright	Visual
Density @ 15°C	g/cm <sup>3</sup>	0.866	ASTM D-4052
Viscosity @ 40°C	cSt	60 – 80	ASTM D-445
Viscosity @ 100°C	cSt	8 – 11	ASTM D-445
Viscosity Index, min.	-	115	ASTM D- 2270
Flash Point min.	°C	110	ASTM D-92
Pour Point, max.	°C	-18	ASTM D-97
Code	-	300	-

TOP BIKE LIFE

FULLY SYNTHETIC

TTC(2T)