

DISCRIPTION

POWER BIKE LIFE engine oil is a high-performance two-stroke lubricant formulated for modern motorcycles and scooters. It provides excellent engine protection, reduced exhaust smoke, and superior engine cleanliness under high-temperature and high-speed operating conditions.

POWER BIKE LIFE is formulated using high-quality base oils and advanced low-ash additive technology to deliver superior lubrication and outstanding engine protection for modern two-stroke engines. The formulation helps maintain excellent piston cleanliness, minimizes carbon deposits, and protects critical engine components against wear, corrosion, and scuffing.

The oil ensures smooth engine operation, reduced exhaust smoke, and improved combustion efficiency. Its advanced detergency system helps prevent piston ring sticking and exhaust port blockage, while the balanced formulation ensures good fuel-oil mixing and reliable lubrication during high-speed and high-temperature engine operation.

APPLICATION

POWER BIKE LIFE is recommended for use in

- Modern two-stroke motorcycles and scooters
- Air-cooled and water-cooled two-stroke engines
- Oil injection and premix lubrication systems
- High-performance two-stroke engines
- Small engines requiring API TC, JASO FC or FD performance levels

BENEFITS

- Excellent engine protection against wear and scuffing
- Superior piston cleanliness and deposit control
- Low smoke formulation for cleaner exhaust emissions
- Prevents piston ring sticking and exhaust port blockage
- Excellent fuel-oil mixing properties
- Improved combustion efficiency
- Protects against rust and corrosion
- Extends engine service life

PRODUCT DATA SHEET



Performance

- API TC
- JASO FC / JASO FD
- ISO-L-EGC / ISO-L-EGD

Packaging: 1Q,1L,4Q, 4L,5Q, 5L, 18L, 20L, 25L, Drums, IBC.

Specification

Test Parameter	Units	Test Limits	Test Method
Appearance	-	Clear & Bright	Visual
Density @ 15°C	g/cm ³	0.866	ASTM D-4052
Viscosity @ 40°C	cSt	60 – 80	ASTM D-445
Viscosity @ 100°C	cSt	8 – 11	ASTM D-445
Viscosity Index, min.	-	115	ASTM D- 2270
Flash Point min.	°C	110	ASTM D-92
Pour Point, max.	°C	-18	ASTM D-97
Code	-	302	-

POWER BIKE LIFE
MONO-GRADE
TC(2T)