

COMPRESSOR LIFE
SYNTHETIC TECHNOLOGY
ISO VG 68

DISCRIPTION

COMPRESSOR LIFE is a high-quality lubricant formulated from carefully selected base oils and advanced additives to provide reliable lubrication, excellent oxidation resistance, and effective protection for air compressors operating under various conditions.

COMPRESSOR LIFE is specially formulated to meet the lubrication requirements of modern air compressor systems. It is manufactured using high-quality base oils and performance additives that help provide excellent protection against wear, oxidation, rust, and deposit formation.

The oil offers good thermal stability and oxidation resistance, helping to maintain clean compressor components and extend service life. Its effective demulsibility allows quick separation from water, while the low foaming tendency ensures smooth compressor operation.

APPLICATION

COMPRESSOR LIFE is recommended for use in

- Rotary screw air compressors
- Rotary vane compressors
- Reciprocating air compressors
- Industrial air compressor systems
- Portable and stationary compressor units

BENEFITS

- Good oxidation and thermal stability
- Reliable protection against wear and corrosion
- Helps minimize sludge and deposit formation
- Good water separation properties
- Low foaming characteristics
- Helps maintain compressor efficiency
- Suitable for a wide range of compressor types

PRODUCT DATA SHEET



Performance

- DIN 51506 VDL
- ISO 6743-3A DAJ

AVAILABILITY

ISO VG Grade 32, 46, 68, 100 and 150

Packaging: 1Q,1L,4Q, 4L,5Q, 5L, 18L, 20L, 25L, Drums, IBC.

Specification

Test Parameter	Units	Test Limits	Test Method
ISO VG		68	-
Appearance	-	C&B	Visual
Density @ 15°C	g/cm ³	0.861	ASTM D-4052
Viscosity @ 40°C	mm ² /s	62.5-71.5	ASTM D-445
Viscosity @ 100°C	mm ² /s	7.8	ASTM D-445
Viscosity Index	-	105	ASTM D- 2270
Flash Point(COC)	°C	220	ASTM D-92
Pour Point	°C	-18	ASTM D-97
CODE		803/3	

COMPRESSOR LIFE
SYNTHETIC TECHNOLOGY
ISO VG 68