

### DISCRIPTION

**COMPRESSOR LIFE** is a high-quality lubricant formulated from carefully selected base oils and advanced additives to provide reliable lubrication, excellent oxidation resistance, and effective protection for air compressors operating under various conditions.

**COMPRESSOR LIFE** is specially formulated to meet the lubrication requirements of modern air compressor systems. It is manufactured using high-quality base oils and performance additives that help provide excellent protection against wear, oxidation, rust, and deposit formation.

The oil offers good thermal stability and oxidation resistance, helping to maintain clean compressor components and extend service life. Its effective demulsibility allows quick separation from water, while the low foaming tendency ensures smooth compressor operation.

### APPLICATION

**COMPRESSOR LIFE** is recommended for use in

- Rotary screw air compressors
- Rotary vane compressors
- Reciprocating air compressors
- Industrial air compressor systems
- Portable and stationary compressor units

### BENEFITS

- Good oxidation and thermal stability
- Reliable protection against wear and corrosion
- Helps minimize sludge and deposit formation
- Good water separation properties
- Low foaming characteristics
- Helps maintain compressor efficiency
- Suitable for a wide range of compressor types

## PRODUCT DATA SHEET



### Performance

- DIN 51506 VDL
- ISO 6743-3A DAJ

### AVAILABILITY

ISO VG Grade 32, 46, 68, 100 and 150

**Packaging:** 1Q,1L,4Q, 4L,5Q, 5L, 18L, 20L, 25L, Drums, IBC.

### Specification

Test Parameter	Units	Test Limits	Test Method
ISO VG		32	-
Appearance	-	C&B	Visual
Density @ 15°C	g/cm <sup>3</sup>	0.861	ASTM D-4052
Viscosity @ 40°C	mm <sup>2</sup> /s	28.8-35.2	ASTM D-445
Viscosity @ 100°C	mm <sup>2</sup> /s	5.6	ASTM D-445
Viscosity Index	-	105	ASTM D- 2270
Flash Point(COC)	°C	220	ASTM D-92
Pour Point	°C	-18	ASTM D-97
<b>CODE</b>		803/1	

COMPRESSOR LIFE  
SYNTHETIC TECHNOLOGY  
ISO VG 32