

DISCRIPTION

TURBINE LIFE PLUS HVI is a premium performance lubricant formulated with high quality synthetic base oils and advanced additive technology. It is designed to provide excellent oxidation stability, superior thermal resistance, and outstanding protection for modern steam, gas, and combined cycle turbines operating under severe conditions.

TURBINE LIFE PLUS is a high-performance turbine lubricant developed using advanced synthetic base oils with naturally high viscosity index and carefully selected additive systems. The formulation ensures excellent oxidation resistance, superior thermal stability, and long service life in demanding turbine applications.

This oil provides exceptional protection against rust, corrosion, and wear while maintaining excellent water separation and air release characteristics. The high viscosity index allows stable lubrication across a wide temperature range, ensuring reliable performance during both start-up and continuous operation.

APPLICATION

TURBINE LIFE PLUS is recommended for use in

- Steam turbines
- Gas turbines
- Combined cycle turbines
- Industrial turbine systems requiring high performance lubricants
- Circulating lubrication systems
- Turbine bearings and auxiliary equipment
- Power generation turbines operating under severe temperature conditions

BENEFITS

- Excellent oxidation and thermal stability for extended oil life
- High viscosity index for stable performance across wide temperature ranges
- Superior protection against rust and corrosion
- Excellent water separation properties
- Outstanding air release characteristics to minimize foam formation
- Helps maintain system cleanliness and reduces sludge and varnish formation
- Long service intervals and reduced maintenance costs
- Reliable lubrication for modern high-performance turbine systems

PRODUCT DATA SHEET



AVAILABILITY

ISO VG Grade 32, 46 and 68

Packaging: 1Q,1L,4Q, 4L,5Q, 5L, 18L, 20L, 25L, Drums, IBC.

Specification

Test Parameter	Units	Test Limits	Test Method
ISO VG		46	-
Appearance	-	C&B	Visual
Density @ 15°C	g/cm ³	0.861	ASTM D-4052
Viscosity @ 40°C	mm ² /s	41.4-50.6	ASTM D-445
Viscosity @ 100°C	mm ² /s	6.8	ASTM D-445
Viscosity Index	-	140	ASTM D- 2270
Flash Point(COC)	°C	230	ASTM D-92
Pour Point	°C	-40	ASTM D-97
CODE		805/2	

TURBINE LIFE PLUS
ISO VG 46
HVI-FULLY SYNTHETIC