

RUVO

Surface & Pendant LED Downlight



RUVO is a compact, IP65-rated surface-mounted LED luminaire designed for reliable performance and clean architectural integration. Featuring a durable aluminium body, glare-controlled optics (UGR <19), and COB LED technology, it delivers precise, comfortable illumination for accent and general lighting. Available in multiple wattages, beam angles, and classic finishes, RUVO suits retail, hospitality, gallery, and residential applications.

GENERAL SPECS

Product Name	RUVO
Mounting Type	Surface Mounted
Housing Material	Aluminum
Finish Options	Black / White
Optic Type	Deep Recessed Reflector
Glare Control	Low Glare (Deep-set optic)
Protection Rating	IP65
Installation Area	Indoor / Semi-Outdoor
Driver Type	Integrated
Dimming Options	On/Off / 0–10V / DALI
Operating Voltage	220–240V AC
Frequency	50/60 Hz
Lifetime	≥50,000 hours (L80)



Optional Accessory:
Pendant Suspension Kit

RUVO

Surface & Pendant LED Downlight



Wattage	Lumen Output	CCT	Beam Angle	CRI	Diameter	Height
10W	900–1000 lm	3000K / 4000K	24° / 36°	≥90	Ø85 mm	90 mm
15W	1300–1500 lm	3000K / 4000K	24° / 36°	≥90	Ø95 mm	100 mm
20W	1800–2000 lm	3000K / 4000K	36° / 60°	≥90	Ø110 mm	110 mm

