

Regenerative Dryers

Features:

- Spin on regenerative style desiccant canisters
- Up to 80°F dew point depressions
- Housings manufactured from 6061 billet aluminum
- Hard-coat anodized for max corrosion resistance
- Molecular sieve desiccant
- Solenoid valve timer
- Automatic drains
- Purge exhaust mufflers
- 2-stage pre-filtration
- Dew points as low as -60°F
- Tank mountable up to 100 CFM systems
- Easy installation
- Tank mountable up to 100 CFM systems
- Multiple control voltage options (120V Standard)
- 1/3 the size of a standard desiccant air dryer
- Easy maintenance system
- Tank mountable up to 100 CFM systems

Options:

- NEMA 4 control box
- No yellow metals
- 3 valve dryer bypass for maintenance



| Model | Max Flow @ 70% Duty Cycle | Max Flow @ 100% Duty Cycle | Inlet/Outlet NPT | Purge CFM Required |
|-----------------|---------------------------|----------------------------|--------------------|--------------------|
| SODD5HP | 17 CFM | 12 CFM | 1/4" in / 1/2" out | 1.1 @ 175 PSI |
| SODD10HP | 40 CFM | 28 CFM | 1" | 1.5 @ 100 PSI |
| SODD15HP | 60 CFM | 42 CFM | 1" | 3.4 @ 100 PSI |
| SODD20HP | 80 CFM | 56 CFM | 1" | 1.5 @ 100 PSI |
| SODD30HP | 120 CFM | 84 CFM | 1" | 6 @ 100 PSI |
| SODD40HP | 160 CFM | 112 CFM | 1" | 17 @ 150 PSI |
| SODD50HP | 240 CFM | 168 CFM | 2" | 17.2 @ 150 PSI |

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 4-2025



Scan to visit our website

