

AIRTITE PIPE

A Stainless Steel Piping System from Compressed Air Systems

Fast and Easy Installation with Press Fittings

Secure, leak-free joints that last. Airtite Pipe and fittings connect in 15 seconds or less, with no special training required

Durable & Dynamic

Maximum working pressure of 16Bar/235PSI

Working temperature range of -4 °F/-20°C to 176 °F/80 °C

ASME B31.1 & ASME B31.3 certified

Fluid Group: 2

Pipe and Fittings from 1/2" to 6"

With a complete range of fitting types and sizes, we have everything you need to get the job done

Corrosion Free

Airtite Pipe and fittings are stainless steel, made to stand up to the toughest jobs while keeping its clean appearance

Cost Effective

Save on material costs compared to copper and aluminum



- Connections can be made wet or dry for quick repairs on existing systems
- Make secure press connections in fifteen seconds or less
- Press technology eliminates the need for soldering
- More than 300 different fitting configurations
- Configurations include couplings, elbows, reducers, tees, adapters, unions, caps, flanges, and valves
- ASME B31.1 & ASME B31.3 certified

- Maximum working pressure of 16Bar/235PSI
- Working temperature range of -4°F/-20°C to 176°F/80°C
- Rated for Fluid Group 2
- PED/ASME rated working temperature range -4°F to 180°F
- Designed to convey a variety of fluids, including compressed air, natural gas, inert gases, chilled water, hot water, process water, waste water, chemicals, acid solutions, caustic solutions, low-pressure steam (15 PSI max), and hydraulic oils

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 8-2025



Scan to visit our website

