

13-14 HP | 15.9 CFM Engine Driven Reciprocating Compressor



Features

- Heavy-duty two-stage solid cast iron pump
- Industrial-duty engine
- Needle bearings and inserts on rods
- Access to compressor valves without compressor head removal
- Alternator on drive engine
- ASME/CRN certified air receiver
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Critical controls protected by compressor base plate
- Disk and spring valves
- Drive engine on left side for safety
- Fully enclosed belt guard
- Full saddle mounting feet instead of pegged mounting feet
- Heavy-duty air filter
- Pilot valve continuous operation
- Stainless steel flexible air lines
- Swedish steel valves
- Torrington needle bearings
- 2-groove B width drive pulley
- 2-piece tank/top plate design

22.1 CFM @
125 PSI

15.9 CFM @
175 PSI



Elite Features

- All basic features
- Automatic tank drain
- Belt guard after cooler
- On-board battery mounted and wired (no truck wiring needed)
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada

Model	HP	CFM @ 100 PSI	CFM @ 175 PSI	Engine Brand	Starter	Tank	LxWxH	Weight
C130GEH33	13	22.1	15.9	CRX	Electric	30 Gallon Horizontal	42x22x42	650
C130GEX33	13	22.1	15.9	Honda	Electric	30 Gallon Horizontal	45x21x41	650
C140GEC33	14	22.1	15.9	Kohler	Electric	30 Gallon Horizontal	44x21x42	650

Add -E after model number to make Elite Model. Available in basemount configuration without tank.

No Start Up Kit Required

Lifetime Parts Warranty Available

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 10-2025



Scan to visit our website

