

50 HP Permanent Magnet Rotary Screw Compressor



Features

- Liquid cooled Permanent Magnet drive motor
- 50% oversized air/oil cooler to allow for higher ambient conditions
- Direct drive for zero power loss — no bearings, belts, or couplers
- IE4 Super Premium Efficiency standard for energy savings
- IP65 protection against dust and moisture
- Variable speed drive
- Integrated flux vector inverter
- Wide voltage design meets C3 and EMC standards
- UL Certified electrical controls
- VSD controlled cooling fan
- Built in DC Reactor
- 7 inch full color touch screen
- RS485 connectivity for system integration
- Closed Loop dynamic controls
- Quiet thermostatically controlled cooling fan
- Compressor airend speed 3500 RPM or less
- Easy controller interface

CRD Package Features

- ASME/CRN certified air receiver
- Automatic tank drain
- Refrigerated air dryer
- SMART contact control
- Vibration isolation pads
- Freight pre-paid in the 48 states & southern Canada

72 dBA

212 CFM @
120 PSI

187 CFM @
150 PSI



Model	HP	CFM @ 120 PSI	CFM @ 150 PSI	Voltage	dBA	Tank	LxWxH	Weight
RS50ENC-PM	50	212	187	208-230/480/3	72±3	N/A	40x55x60	1499

To make package "CRD" configuration add -CRD to the end of the model number

No Start Up Kit Required

Lifetime Parts Warranty Available

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 10-2025



Scan to visit our website

