

39 CFM Gas/Diesel Engine Driven Rotary Screw Compressor



Features

- Heavy-duty single stage rotary screw airend
- Industrial-duty drive engine
- Heavy duty air filter
- Spin on oil filter
- Spin on separator
- ASME/CRN certified air receiver
- Drive engine on left side for safety
- Easy to read and access gauges
- Easy to remove bolt on oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Fully enclosed belt guard
- Full saddle mounting feet instead of pegged mounting feet
- Operating pressures from 100-190 PSI available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- 220 PSI maximum working pressure

Elite Features

- Air/oil cooler
- Battery mounted and wired
- SIMPLEX controls
- Tank discharge ball valve
- Vibration isolation pads
- Free freight in the 48 states & southern Canada

40 CFM @
100 PSI

39 CFM @
150 PSI



Model	HP	CFM @ 100 PSI	CFM @ 150 PSI	Engine Brand	Starter	Tank	LxWxH	Weight
RS180GEH33	18	40	39	Honda	Electric	30 Gallon	48x30x48	700
RS180GED33	17	40	39	Kohler Diesel	Electric	30 Gallon	48x36x48	725

Add -E after model number to make Elite Model. Available in basemount configuration without tank.

No Start Up Kit Required

Lifetime Parts Warranty Available

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 10-2025



Scan to visit our website

