

7.5 HP Enclosed Duplex Rotary Screw



70 dBA

52 cfm @ 125 psi

58 cfm @ 125 psi

Features

- Airend manufactured with German rotary screw components
- Air/oil cooler
- ASME powder coated air receiver
- Automatic tank drain
- Baldor electric motors
- Easy to read and access gauges
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Grasshopper style tank
- Heavy-duty air filter
- IEC contactors
- Omega profile rotors
- Single control solenoid operation
- SMART contact controls
- Sound dampening enclosure
- Spin on oil filter
- Spin on separator
- Stainless steel discharge lines
- Timed shutdown
- UL control components
- Vibration isolation pads
- 220 PSI maximum working pressure



Model Number	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
DRS101ENC-CRD	1	208-230	120 Gallon Horizontal	98	36	78	104	N/A
DRS103ENC-CRD	3	208-230/460-480	120 Gallon Horizontal	98	36	78	56	28

No Start Up Kit Required

Optional Lifetime Parts Warranty Available

See catalog for additional options

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 7-2024

