

# 5 HP Enclosed Duplex Rotary Screw



70 dBA

32 cfm @ 125 psi

38 cfm @ 125 psi

## Features

- Airend manufactured with German rotary screw components
- Air/oil cooler
- ASME powder coated air receiver
- Automatic tank drain
- Baldor electric motors
- Easy to read and access gauges
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Grasshopper style tank
- Heavy-duty air filter
- IEC contactors
- Omega profile rotors
- Single control solenoid operation
- SMART contact controls
- Sound dampening enclosure
- Spin on oil filter
- Spin on separator
- Stainless steel discharge lines
- Timed shutdown
- UL control components
- Vibration isolation pads
- 220 PSI maximum working pressure



Model Number	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
DRS51ENC-CRD	1	208-230	120 Gallon Horizontal	98	36	78	48	N/A
DRS53ENC-CRD	3	208-230/460-480	120 Gallon Horizontal	98	36	78	32	16

No Start Up Kit Required

Optional Lifetime Parts Warranty Available

See catalog for additional options

## Compressed Air Systems

Simplicity. It's What We Do.

[compressed-air-systems.com](http://compressed-air-systems.com) | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 7-2024

