25 HP | 102 CFM
Rotary Screw Compressor

80 dBA	108 CFM @ 125 PSI	102 CFM @ 150 PSI

Features
- Heavy-duty single stage rotary screw airend
- Air/oil cooler
- Automatic belt tensioning
- Easy to read and access gauges
- Easy to access oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy-duty air filter
- Operating pressures from 100-190 PSI available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin on oil filter
- Spin on separator
- TEFC drive motor (3 phase only)
- 2-piece tank/top plate design
- UL control components
- 220 PSI maximum working pressure
- Plato Smart Touchscreen controls with real-time monitoring, easy troubleshooting, maintenance reminders, and remote accessibility

Elite Features
- Automatic tank drain
- SMART contact controls
- Vibration isolation pads
- Tank discharge ball valve
- Freight pre-paid in the 48 states & southern Canada


Belt guard mounted air/oil cooler

Model	HP	CFM @ 125 PSI	CFM @ 150 PSI	Voltage	Tank	L×W×H
RS253H126-S	25	108	102	208-230/480/3	120 Gallon Horizontal	76×36×60
Add -E after model number to make Elite Model						

No Start Up Kit Required **Lifetime Parts Warranty Available**

Compressed Air Systems
Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 01-2026

Scan to visit our website