

40 CFM Hydraulic Motor Driven Rotary Screw Compressor

45 CFM @
100 PSI

40 CFM @
150 PSI

Features

- Heavy-duty single stage rotary screw airend
- ASME/CRN certified safety valves
- Hydraulic fluid flow regulator
- Hydraulic fluid pressure regulator
- Hydraulic fluid bypass valve
- NEMA 4 load/unload switch
- External NEMA 4 on/off switch
- All hydraulic fluid and air connections on same side
- CAS SMART fluid control system
- Compressor load/unload operation
- Easy to remove compressor cover
- Heavy-duty industrial rotary screw airend
- Intake filter silencer
- Steel mounting plate
- Vibration mounting pads
- 12 volt compressor air & oil cooler pack*
- 12 volt control system**

Package Options

- Cold weather heating package
- Cover color change
- High ambient temperature cooling package
- Hose reels
- Hydraulic fluid cooler
- Tank mounted
- 24 volt operation
- 110 volt operation

* Cooler pack to be mounted external to compressor system. 12 volt control voltage connection to be supplied by vehicle/equipment compressor is mounted to.

Do not let hydraulic fluid exceed 190° F.



Model	CFM @ 100 PSI	CFM @ 150 PSI	Hydraulic PSI required	GPM Hydraulic Flow Required	LxWxH	Weight
H-BM40RS	45	40	2250	13	32x20x26	400

Dimensions are representatives of package dimensions not total space required for mounting.

No Start Up Kit Required

Lifetime Parts Warranty Available

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 01-2026



Scan to visit our website

