

13 HP | 32 CFM Engine-Driven Rotary Screw Compressor

36 CFM @
100 PSI

32 CFM @
150 PSI

Features

- Heavy-duty single stage rotary screw airend
- Industrial-duty drive engine
- Heavy-duty air filter
- Spin on oil filter
- Spin on separator
- ASME/CRN certified air receiver
- Drive engine on left side for easy access and safety
- Easy to read and access gauges
- Easy to remove bolt on oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Fully enclosed belt guard
- Full saddle mounting feet instead of pegged mounting feet
- Operating pressures from 100-190 PSI available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- 220 PSI maximum working pressure

Elite Features

- Battery mounted and wired
- Tank discharge ball valve
- Vibration isolation pads
- Free freight in the 48 states & southern Canada



Model	HP	CFM @ 100 PSI	CFM @ 150 PSI	Engine Brand	Starter	Tank	LxWxH	Weight
RS130GEH33	13	36	32	Honda	Electric	30 Gallon	45x25x46	500

Add -E after model number to make Elite Model. Available in basemount configuration without tank.

No Start Up Kit Required

Lifetime Parts Warranty Available

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 01-2026



Scan to visit our website

