

39 CFM Enclosed Engine-Driven Rotary Screw Compressor

47 CFM @
100 PSI

39 CFM @
150 PSI

Features

- Heavy-duty single stage rotary screw airend
- Industrial grade drive engine
- Electric start drive engine
- Engine idle control to meet air demand
- High oil temperature shut down
- High air temperature shut down
- JIC quick connect air & oil lines
- Low engine oil shutdown
- Quick service compressor filters
- Vibration mounting pads
- 12 Volt compressor air & oil cooler pack*
- 220 PSI maximum working pressure

Package Options

- Battery for engine electric start
- Cold weather heating package
- Compressed air regulator control pack
- Cover color change
- Drive engine control extension
- High ambient temperature cooling package
- 6 or 12 gallon EPA, DOT rated fuel cells
- 6 or 30 gallon air storage tank

* Cooler pack to be mounted external to compressor system. 12 volt control voltage connection to be supplied by vehicle/equipment compressor is mounted to.



Model	CFM @ 100 PSI	CFM @ 150 PSI	Engine Brand	Auxiliary Fuel Tank Required	LxWxH
RS180GEH-ENC	47	39	Honda	Yes	40x20x26
RS180GEC-ENC	47	39	Kohler	Yes	40x20x26

Dimensions are representatives of package dimensions not total space required for mounting.

No Start Up Kit Required

Lifetime Parts Warranty Available

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 01-2026



Scan to visit our website

