

20 HP | 78 CFM Enclosed Rotary Screw Compressors

Features

- Heavy-duty single stage rotary screw airend
- Heavy-duty powder-coated steel enclosure with sound dampening panels and access doors on all sides
- Air/oil cooler
- Automatic belt tensioning
- Easy to read and access gauges
- Easy to access oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy-duty air filter
- Operating pressures from 100-190 PSI available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin on oil filter
- Spin on separator
- TEFC drive motor (3 phase only)
- 2-piece tank/top plate design
- UL control components
- Plato Smart Touchscreen controls with real-time monitoring, easy troubleshooting, maintenance reminders, and remote accessibility

CRD Package Features

- ASME/CRN certified air receiver
- Automatic tank drain
- Refrigerated air dryer
- Stainless steel discharge lines
- Vibration isolation pads
- Free freight in the 48 states & southern Canada

73 dBA

88 CFM @
125 PSI

78 CFM @
150 PSI



Model	HP	CFM @ 125 PSI	CFM @ 150 PSI	Dryer CFM	Voltage	Tank	LxWxH
RS203ENC6-S	20	88	78	N/A	208-230/480/3	N/A	52x48x40
RS203ENC6-S-CRD	20	88	78	75	208-230/480/3	80 Gallon Horizontal	80x48x68

No Start Up Kit Required

Lifetime Parts Warranty Available

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 01-2026



Scan to visit our website

