

13 HP | 23 CFM Engine-Driven Cube Air System Pressure Lubricated Reciprocating Compressor

23 CFM @ 175 PSI

Features

- Pressure lubricated reciprocating compressor pump
- Centrifugal unloader
- Disc and spring valves
- Discharge cooling manifold
- Easy open inline check valve
- Easy service belt guard
- Easy to read oil sight glass
- Easy service reciprocating pump platform
- Extended oil drain tube
- Inner stage cooler
- Minimal floor space foot print
- Multiplexing capability
- Rigid steel frame construction
- Self tensioning electric motor base

Optional Package Features

- Coalescing filtration
- Desiccant air dryer
- Electronic automatic tank drain kit (shipped loose for installation on site)
Kit includes: drain, 1/4 pipe street 90 elbow, 1/4 pipe 6 inch nipple
- Enrollment in factory extended service program
- Enrollment in factory extended warranty plan
- Particulate filtration
- Quick Install Kit Includes:
8 feet electrical cord with plug, 6 feet compressor to tank air line JIC fittings, 6 feet tank to facility air line JIC fittings
- Reciprocating Pump Enclosure for noise reduction
- Refrigerated air dryer
- 30, 60, 80, 120, gallon storage tank (200 psi MWP, ASME, CRN)

Elite Features

- All basic compressor features
- Belt guard mounted air after cooler
- Low oil monitor
- High-temp stainless steel flex discharge line
- Vibration isolation mounting pads
- Freight pre-paid in standard freight area



Model	HP	CFM @ 125 PSI	CFM @ 175 PSI	Brand	Starter	LxWxH	Weight
Q-C130-PL	13	24	23	Honda	Electric	20x20x45	350
Q-C140-PL	13	24	23	Kohler	Electric	20x20x45	350

Add -E after model number to make Elite Model

No Start Up Kit Required

Lifetime Parts Warranty Available

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 01-2026

