

# 5 HP | 16 CFM Two-Stage Reciprocating Compressor

## Features

- Heavy-duty two-stage solid cast iron pump
- Reed valves
- Bearings on both ends of the crank shaft
- Needle bearings, and inserts on rods
- All UL electrical controls
- ASME/CRN certified air receiver
- Auto start/stop
- Heavy-duty air filter
- Industrial grade electric motor
- Stainless steel flexible air lines
- TEFC drive motor (3 phase only)
- Torrington needle bearings
- 1-groove A width motor pulley
- 2-piece tank/top plate design

18.2 CFM  
@ 40 PSI

16 CFM  
@ 175 PSI



Model	HP	CFM @ 40 PSI	CFM @ 175 PSI	Voltage	Tank	LxWxH	Weight
B51V33	5	18.2	16	208-230/1	30 Gallon Vertical	27x24x44	475
B51V63	5	18.2	16	208-230/1	60 Gallon Vertical	27x25x72	500
B51V83	5	18.2	16	208-230/1	80 Gallon Vertical	29x24x70	525

No Start Up Kit Required

Lifetime Parts Warranty Available

## Compressed Air Systems

Simplicity. It's What We Do.

[compressed-air-systems.com](http://compressed-air-systems.com) | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 09-2025



Scan to visit our website

