

10 HP | 70.8 CFM Duplex Pressure Lubricated Reciprocating Compressors

Features


- Heavy-duty pressure lubricated two-stage solid cast iron pumps
- Disk and spring valves
- Centrifugal unloaders
- Bearings on both ends of the crank shafts
- Needle bearings, and inserts on rods
- Torrington needle bearings
- Swedish steel valves
- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME/CRN certified air receiver
- Auto start/stop
- Fully enclosed belt guards
- Heavy-duty air filters
- Industrial grade electric motors
- TEFC drive motors (3 phase only)
- Magnetic starter mounted and wired
- Stainless steel flexible air lines
- 2-groove B width motor pulley
- 2-piece tank/top plate design

Elite Features

- All basic features
- Automatic tank drain
- Belt guard mounted after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada

Time Delay
70.8 CFM @
175 PSI

Alternating
35 CFM @
175 PSI



Air cooled after cooler on Elite models



Model	HP	CFM @ 100 PSI	CFM @ 175 PSI	Voltage	Tank	LxWxH
DB101H126-PL	10	73.8	70.8	208-230/1	120 Gallon Horizontal	88x29x53
DB103H126-PL	10	73.8	70.8	208-230/480/3	120 Gallon Horizontal	88x29x53
DB101H246-PL	10	73.8	70.8	208-230/1	240 Gallon Horizontal	86x40x58
DB103H246-PL	10	73.8	70.8	208-230/480/3	240 Gallon Horizontal	86x40x58

Add -E after model number to make Elite Model

No Start Up Kit Required

Lifetime Parts Warranty Available

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 01-2026



Scan to visit our website

