

15 HP | 80.2 CFM Duplex Pressure Lubricated Reciprocating Compressor

Features


- Heavy-duty pressure lubricated two-stage solid cast iron pumps
- Disk and spring valves
- Centrifugal unloaders
- Bearings on both ends of the crank shafts
- Needle bearings, and inserts on rods
- Torrington needle bearings
- Swedish steel valves
- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME/CRN certified air receiver
- Auto start/stop
- Fully enclosed belt guards
- Heavy-duty air filters
- Industrial grade electric motors
- TEFC drive motors (3 phase only)
- Magnetic starter mounted and wired
- Stainless steel flexible air lines
- 2-groove B width motor pulley
- 2-piece tank/top plate design

Elite Features

- All basic features
- Automatic tank drain
- Belt guard mounted after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada

Time Delay
80.2 CFM @
175 PSI

Alternating
40.1 CFM @
175 PSI



Air cooled after cooler on Elite models



| Model | HP | CFM @ 100 PSI | CFM @ 175 PSI | Voltage | Tank | LxWxH |
|--------------|----|---------------|---------------|---------------|-----------------------|----------|
| DB153H246-PL | 15 | 82 | 80.2 | 208-230/480/3 | 240 Gallon Horizontal | 85x50x70 |

Add -E after model number to make Elite Model

No Start Up Kit Required

Lifetime Parts Warranty Available

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 01-2026



Scan to visit our website

