

3.9 HP | 12 CFM Battery Powered Reciprocating Compressor

Features

- 60 minutes of run time under standard duty cycle
- Includes two 8 Ah 82v commercial batteries
- Industrial duty electric drive motor
- Auto overheating safety shutdown
- Heavy duty solid cast iron pump with reed valves
- Quiet and smooth operation
- Rapid Recharge battery system
- Dual battery charger
- 200 PSI rated tank
- Oversized ag style wheel
- 2 Piece tank/top plate design
- Mounted vibration isolation system
- Bolt on handles
- ½ inch pressure regulator
- Two 3/8 inch quick connections
- Stainless steel flexible air lines
- Standard size JIC air line connections

Options

- Additional batteries for extra 1 hours of run time
- Belt guard aftercooler
- Automatic tank drain
- Package enclosure
- Duplex configuration with 24 CFM @ 125 PSI

75 dBA

12 CFM
@ 125 PSI



Model	HP	ACFM @ 125 PSI	Tank Size	LxWxH	Weight
P3EBP11	3.9	12	10 Gallon Portable	47x20x28	270
P3EBP21	3.9	12	20 Gallon Portable	42x24x37	270
P3EBP31	3.9	12	30 Gallon Horizontal	42x24x42	290

No Start Up Kit Required

Lifetime Parts Warranty Available

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 01-2026



Scan to visit our website

