

7.5 HP | 52 CFM Duplex Rotary Screw Compressor


75 dBA

58 CFM @
125 PSI

52 CFM @
150 PSI

Features

- Heavy-duty single stage rotary screw airends
- Air/oil coolers
- Automatic belt tensioning
- Easy to read and access gauges
- Easy to access oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy-duty air filters
- Operating pressures from 100-190 PSI available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin on oil filters
- Spin on separators
- TEFC drive motors (3 phase only)
- 2-piece tank/top plate design
- UL control components
- 220 PSI maximum working pressure
- Plato Smart Touchscreen controls with real-time monitoring, easy troubleshooting, maintenance reminders, and remote accessibility



Belt guard mounted air/oil cooler

Elite Features

- Automatic tank drain
- SMART contact controls
- Vibration isolation pads
- Tank discharge ball valve
- Freight pre-paid in the 48 states & southern Canada



Model	HP	CFM @ 125 PSI	CFM @ 150 PSI	Voltage	Tank	LxWxH
DRS71H123-S	7.5	58	52	208-230/1	120 Gallon Horizontal	85x37x54
DRS73H123-S	7.5	58	52	208-230/480/3	120 Gallon Horizontal	85x37x54

Add -E after model number to make Elite Model

No Start Up Kit Required

Lifetime Parts Warranty Available

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 06-2026



Scan to visit our website

