


18 HP | 34 CFM Diesel Engine-Driven Reciprocating Compressor

34 CFM @ 175 PSI

Features

- Heavy-duty two-stage solid cast iron pump
- Industrial-duty engine
- Needle bearings and inserts on rods
- Access to compressor valves without compressor head removal
- Alternator on drive engine
- ASME/CRN certified air receiver
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Critical controls protected by compressor base plate
- Disk and spring valves
- Drive engine on left side for safety
- Fully enclosed belt guard
- Full saddle mounting feet instead of pegged mounting feet
- Heavy-duty air filter
- Pilot valve continuous operation
- Stainless steel flexible air lines
- Swedish steel valves
- Torrington needle bearings
- 2-groove B width drive pulley
- 2-piece tank/top plate design



Air cooled after cooler on Elite models



Elite Features

- All basic features
- Automatic tank drain
- Belt guard after cooler
- On-board battery mounted and wired (no truck wiring needed)
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada

Model	HP	CFM @ 100 PSI	CFM @ 175 PSI	Engine Brand	Starter	Tank	LxWxH	Weight
C180GED36HC	18	36	34	Kohler Diesel	Electric	30 Gallon Horizontal	53x31x48	940

Add -E after model number to make Elite Model

No Start Up Kit Required

Lifetime Parts Warranty Available

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 06-2026



Scan to visit our website

