



Each Roll:
38" x 100'
(316 Sq. ft²) 12 lbs



Overwrap 100

Ideal for Homebuilders
& Light Commercial Projects.

Upgrade your job site protection from paper to Overwrap 100! High water and tear resistance will keep your site entryways safe from wet boots, mud and debris. The weight of Overwrap 100 makes it ideal to lay in primary walking paths, the strength of the reinforced synthetic fabric stands up to heavy foot traffic, rubber wheel traffic, tools and construction activity!



WWW.OVERWRAP.NET



Limited Warranty

PRODUCT SHALL BE FREE FROM MANUFACTURING DEFECTS AND CONFORM TO THE PRINTED PRODUCT SPECIFICATIONS. THERE ARE NO WARRANTIES BEYOND THIS EXPRESSED LIMITED WARRANTY. ALL OTHER WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE EXCLUDED. EXCLUDES ANY LIABILITY FOR LOST PROFITS OR ANY OTHER INDIRECT, SPECIAL OR OTHER CONSEQUENTIAL DAMAGES. THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.



800 West 5th Avenue, Suite 212
Naperville, IL 60563
336-250-7862



WWW.OVERWRAP.NET

Installation Instructions



01

Always install Overwrap logo side up.

02

Estimate how much material is required to cover the protected areas.

03

Ensure the surface to be covered is clean – free of dirt, dust and debris.

04

Roll out the Overwrap and cut to the desired length.

05

Stagger adjacent rolls. For rapid installations, overlap material at edges using the blue registration marks as a guideline.

06

Tape seams on surfaces not sensitive to ghosting tape lines with Overwrap SST Heavy Adhesive 3" wide seam tape or equivalent. Where installations require near uniform breathability, utilize Overwrap MVP Tape or equivalent. Use SST & MVP ONLY on Overwrap material.

07

Adhere the Overwrap outside edges to floor and/or surrounding surfaces, using tape with non-transferable adhesive – painter tape or equivalent.

08

Verify tape adherence/ adhesive transfer is within suitable tolerance on site prior to installation.

09

Overwrap is 100% recyclable and can be re-used as suitable.



WWW.OVERWRAP.NET

USE AND HANDLING

- LayLite Technology makes for fast, easier installation of protection saving time and strain!
- LayLite Technology provides reduced memory roll and pull compared to paper products.
- Provide for near uniform drying of sensitive substrates with Overwrap MVP Breathable Seam Tape.
- For non sensitive surfaces, utilize Overwrap SST Seam Tape for maximum bond and durability.
- Overwrap affords a window of opportunity to clear spills. Remove excessive surface contaminants in a timely manner to prevent damage to protected surfaces.

High Performance Floor Protection



BREATHABLE
Will not trap moisture



LIGHTWEIGHT
Easy handling



REPELLENT
Protects against spills



LAYLITE
Lay flat technology



ECO FRIENDLY
100% recyclable



REGISTRATION
For accurate overlap



TEAR RESISTANT
Enhanced support



Specifications

Overwrap 100



Breathable Synthetic Fabric

OW 100

Property	Test Method	
Mil Thickness	ASTM D1777	30 Mils
Basis Weight	ASTM D3776-09	5.28 OSY
MD Tensile Strength @peak	ASTM D5034-09	79.41 lbs
CD Tensile Strength @peak	ASTM D5034-09	56.15 lbs
MD Elongation @peak	ASTM D5034-09	93.90%
CD Elongation @peak	ASTM D5034-09	154.20%

Safeguard what's underneath from scratches, dents, dings and moisture



EASY INSTALL



PROTECTS SURFACE



EASY CLEAN-UP

DESIGNED TO PROTECT:

Carpet Tile | Carpet | Sheet Vinyl | LVT/LVP | Solid Wood | Engineered Wood | Laminates
Polished Concrete | Stained Concrete | Terrazzo | Resinous Floors | Stone | Tile



WWW.OVERWRAP.NET