




**OVERWRAP**<sup>®</sup>  
SYNTHETIC SURFACE PROTECTION



# Overwrap 200

Each Roll:

**38" x 100' (316 Sq. ft<sup>2</sup>) 15 lbs**

## Surface protection for commercial sites

Upgrade your job site protection from heavy paper (38 – 46 mil) to Overwrap 200! High water and tear resistance will keep your site entryways safe from wet boots, mud and debris. Overwrap 200 is ideal to cover and seal complete areas to protect sensitive finishes from trade traffic. The strength of the reinforced synthetic fabric stands up to heavy foot traffic, rubber wheel traffic, tools and construction activity!



# Installation Instructions



## 01

Always install Overwrap logo side up.

## 02

Estimate how much material is required to cover the protected areas.

## 03

Ensure the surface to be covered is clean – free of dirt, dust and debris.

## 04

Roll out the Overwrap and cut to the desired length.

## 05

Stagger adjacent rolls. For rapid installations, overlap material at edges using the blue registration marks as a guideline.

## 06

Tape seams on surfaces not sensitive to ghosting tape lines with Overwrap SST Heavy Adhesive 3" wide seam tape or equivalent. Where installations require near uniform breathability, utilize Overwrap MVP Tape or equivalent. Use SST & MVP ONLY on Overwrap material.

## 07

Adhere the Overwrap outside edges to floor and/or surrounding surfaces, using tape with non-transferable adhesive – painter tape or equivalent.

## 08

Verify tape adherence/ adhesive transfer is within suitable tolerance on site prior to installation.

## 09

Overwrap is 100% recyclable and can be re-used as suitable.



[WWW.OVERWRAP.NET](http://WWW.OVERWRAP.NET)

## USE AND HANDLING

- LayLite Technology makes for fast, easier installation of protection saving time and strain!
- LayLite Technology provides reduced memory roll and pull compared to paper products.
- Provide for near uniform drying of sensitive substrates with Overwrap MVP Breathable Seam Tape.
- For non sensitive surfaces, utilize Overwrap SST Seam Tape for maximum bond and durability.
- Overwrap affords a window of opportunity to clear spills. Remove excessive surface contaminants in a timely manner to prevent damage to protected surfaces.

## High Performance Floor Protection



**BREATHABLE**  
Will not trap moisture



**LIGHTWEIGHT**  
Easy handling



**REPELLENT**  
Protects against spills



**LAYLITE**  
Lay flat technology



**ECO FRIENDLY**  
100% recyclable



**REGISTRATION**  
For accurate overlap



**TEAR RESISTANT**  
Enhanced support



# Specifications

## Overwrap 200




### Breathable Synthetic Fabric

OW 200

Property	Test Method	
Mil Thickness	ASTM D1777	38 Mils
Basis Weight	ASTM D3776-09	6.38 OSY
MD Tensile Strength @peak	ASTM D5034-09	101.56 lbs
CD Tensile Strength @peak	ASTM D5034-09	96.84 lbs
MD Elongation @peak	ASTM D5034-09	116.10%
CD Elongation @peak	ASTM D5034-09	152.80%

## Safeguard what's underneath from scratches, dents, dings and moisture



EASY INSTALL



PROTECTS SURFACE



EASY CLEAN-UP

### DESIGNED TO PROTECT:

Carpet Tile | Carpet | Sheet Vinyl | LVT/LVP | Solid Wood | Engineered Wood | Laminates  
Polished Concrete | Stained Concrete | Terrazzo | Resinous Floors | Stone | Tile



800 West 5th Avenue, Suite 212  
Naperville, IL 60563  
336-250-7862



WWW.OVERWRAP.NET