

TECHNISCHE EIGENSCHAPPEN

TUTELA GREASE MRM 2

ARTIKELCODE: 1874

TOEPASSING

Grease for general lubrication of articulated joints, universal joints, guides, crank mechanisms mounted on Agricultural Machines and Earth Moving Machines. .

SPECIFICATIES

NLGI 2, IVECO 18-1810 KLASSE II, CONTRACTUELE TECH. REF. Nr.I003.E90

OMSCHRIJVING TEST

OMSCHRIJVING TEST	METHODE	EENHEID	TYPISCHE WAARDE
VOORKOMEN	--	--	SMOOTH STRINGY
KLEUR	--	--	BLACK
WORKED PENETRATION (60)	ASTM D 217	mm/10	285
WORKED PENETRATION (100000)	ASTM D 217	mm/10	320
PENETRATION @ - 20°C	ASTM D 217	mm/10	190
DRUPPEL PUNT	ASTM D 566	°C	198
OIL SEPARATION 30h 100°C	ASTM D 6184	%	4
WELDING LOAD	IP 239	kg	280
THICKENER TYPE	--	--	LITHIUM SOAP
OIL TYPE	--	--	MINERAL
FILLER TYPE	--	--	MOLYBDENUM DISULPHIDE

Alle technische informatie wordt als referentie gegeven.