



## FRAGOL 3H WO 68 SPRAY

FRAGOL 3H WO 68 SPRAY is a VG 68 high performance lubricant based on highly purified white oils specifically designed for easy spraying application for machinery in the food, feed, and pharmaceutical industries.

FRAGOL 3H WO 68 SPRAY meets the requirements of FDA 21 CFR 178.3570, FDA 21 CFR 178.3620 and FDA 21 CFR 172.878 and is 3H-registered for processes where direct food contact can occur. All FRAGOL 3H and H1 registered products are manufactured according to ISO 21.469:2006 which supports producers' HACCP and GMP programs. FRAGOL 3H- and H1-lubricants do not contain ingredients of animal origin or genetically modified products and are KOSHER and HALAL certified.

### APPLICATIONS

- Chains and bearings
- Conveyor lines
- Guides
- Slides
- Pneumatic systems
- Household equipment and appliances
- Mechanical harvesters (eg. tea, vegetables, tobacco, etc.)

### BENEFITS

- High corrosion inhibition
- Very low evaporation loss

### TYPICAL FUNCTIONAL FLUID CHARACTERISTICS

FRAGOL 3H WO 68 SPRAY	Value	Unit	Method
Temperature range	0 to 110	°C	-
Appearance	clear liquid	-	visual
Viscosity @ 40 °C	70	mm <sup>2</sup> /s	ASTM D-445
Viscosity @ 100 °C	9.0	mm <sup>2</sup> /s	ASTM D-445
VI	102	-	ASTM D-2270
Density @ 15 °C	0.868	kg/l	ASTM D-1298
Flash point (COC)	240	°C	ASTM D-92
Pour point	-15	°C	ASTM D-5950

### COMPATIBILITY

FRAGOL 3H WO 68 SPRAY is compatible with commonly used seals, gaskets, hoses, and paints. There are no special requirements when replacing PAO or other mineral-based lubricants. Flushing is recommended to remove remaining residues.