



Azurite [GL] Static White

EDGE-LIT GLASS FIXTURE



24V
DC




For use with Light Source.

SPECIFICATIONS

Output Options	50lm/ft		100lm/ft	
Fixture Wattage (White Lens)	0.8W		1.7W	
Max Run Length (White Lens)	45ft		35ft	
Light Color (CCT)	2700K	3000K	3500K	4000K
Color Rendering	95+ CRI, 2-Step			
Lenses	White			
Mounting	Direct Surface Mounting			
Finish	Anodized Silver, Black, White			
Input Voltage	24VDC (Power Supply: 120VAC - 277VAC)			
Dimming	TRIAC, ELV, 0-10V, DMX, DALI, Bluetooth			
Dimensions	12.00" (304.8mm) × 0.98" (25mm) × 0.47" (12mm)			
Production Interval	1.31" (33.3mm)			
Operating Temperature	-4°F (-20°C) to 113°F (45°C)			

DIMENSIONS



PROJECT NAME _____ FIXTURE TYPE _____ LOCATION _____



Azurite [GL] Static White

EDGE-LIT GLASS FIXTURE



AZURITE [GL] STATIC WHITE COMPONENTS

Azurite [GL] Profile



Static White LED Tape - High Density



PROJECT NAME _____

FIXTURE TYPE _____

LOCATION _____



Azurite [GL] Static White

EDGE-LIT GLASS FIXTURE



PART NUMBER EXAMPLE

ILL-AZ01-SW - I - 27K - 50 - WH - SF - SV - 50" - E2 - C
+
PS - UNIV - 24V - 100W - JBOX

PART NUMBER BUILDER

SERIES	DRY/WET	CCT	OUTPUT	LENS	MOUNTING	FINISH
ILL-AZ01-SW -	I -	-	-	WH -	SF -	-
ilLuminate Azurite [GL] Static White	I - Indoor	27K - 2700K 30K - 3000K 35K - 3500K 40K - 4000K	50 - 50lm/ft 100 - 100lm/ft	WH - White	SF - Surface Mount	SV - Anodized Silver BK - Black WH - White
LENGTH (IN)	DIRECTION	START FEED	LENGTH	DIRECTION	END FEED	LENGTH
-	-	-	-	-	-	-
Fixtures will be built as close to the requested length without going over based on 1.31in (33.3mm) production interval.		E - End	Blank - Endcap	E - End	Blank - Endcap	
Lengths longer than 78in will consist of multiple pieces of channel and lens to be assembled in the field to create the complete fixture length.		B - Back	2 - 2ft	B - Back	2 - 2ft	
			5 - 5ft	C - Endcap	5 - 5ft	
			10 - 10ft		10 - 10ft	
			15 - 15ft		15 - 15ft	
			20 - 20ft		20 - 20ft	
			25 - 25ft		25 - 25ft	

POWER SUPPLY

SERIES	CONTROL	VOLTAGE OUTPUT	MAX WATTAGE OUTPUT	FORM
PS -	-	24V -	-	-
ilLuminate AC to DC Constant Voltage Power Supply	UNIV - Universal 5-in-1 DMX - DMX512 Enabled DALI - DALI-2 Enabled BLE - Bluetooth Enabled	24V - 24VDC	30W - 30W 60W - 60W 100W - 100W 200W - 100W x 2 300W - 100W x 3	JBOX - Dry/Damp Rated IP66 - Wet Rated

PROJECT NAME _____ FIXTURE TYPE _____ LOCATION _____