



Azurite [GL] Tunable White

EDGE-LIT GLASS FIXTURE



24V
DC




For use with  Light Source.

SPECIFICATIONS

Output Options	50lm/ft	100lm/ft	
Fixture Wattage (White Lens)	2.2W	4.4W	
Max Run Length (White Lens)	16.4ft	16.4ft	
Light Color (CCT)	1800K - 3000K	1800K - 3500K	1800K - 4000K
Color Rendering	95+ CRI, 3-Step		
Lenses	White		
Mounting	Direct Surface Mounting		
Finish	Anodized Silver, Black, White		
Input Voltage	24VDC (Power Supply: 120VAC - 277VAC)		
Dimming	TRIAC, ELV, 0-10V, DMX, DALI, Bluetooth		
Dimensions	12.00" (304.8mm) × 0.98" (25mm) × 0.47" (12mm)		
Production Interval	1.31" (33.3mm)		
Operating Temperature	-4°F (-20°C) to 113°F (45°C)		

DIMENSIONS



PROJECT NAME _____ FIXTURE TYPE _____ LOCATION _____



Azurite [GL] Tunable White

EDGE-LIT GLASS FIXTURE



AZURITE [GL] TUNABLE WHITE COMPONENTS

Azurite [GL] Profile



Tunable White LED Tape - High Density



PRELIMINARY

PROJECT NAME _____

FIXTURE TYPE _____

LOCATION _____



Azurite [GL] Tunable White

EDGE-LIT GLASS FIXTURE



PART NUMBER EXAMPLE

ILL-RA01-TW - I - 1830K - 200 - WH - MC - BK - 50" - E2 - C
+
PS - UNIV - 24V - 100W - JBOX

PART NUMBER BUILDER

SERIES	DRY/WET	CCT	OUTPUT	LENS	MOUNTING	FINISH
ILL-AZ01-TW -	-	-	-	WH	SF	-
iLuminate Azurite [GL] Tunable White	I - Indoor	1830K - 1800K - 3000K 1835K - 1800K - 3500K 1840K - 1800K - 4000K	50 - 50lm/ft 100 - 100lm/ft	WH - White	SF - Surface Mount	SV - Anodized Silver BK - Black WH - White
LENGTH (IN)			DIRECTION	START FEED LENGTH		END FEED DIRECTION LENGTH
			-	-	-	
Fixtures will be built as close to the requested length without going over based on 1.31in (33.3mm) production interval.			E - End	Blank - Endcap	E - End	Blank - Endcap
Lengths longer than 78in will consist of multiple pieces of channel and lens to be assembled in the field to create the complete fixture length.			B - Back	2 - 2ft	B - Back	2 - 2ft
				5 - 5ft	C - Endcap	5 - 5ft
				10 - 10ft		10 - 10ft
				15 - 15ft		15 - 15ft
				20 - 20ft		20 - 20ft
				25 - 25ft		25 - 25ft
				30 - 30ft		30 - 30ft

POWER SUPPLY

SERIES	CONTROL	VOLTAGE OUTPUT	MAX WATTAGE OUTPUT	FORM
PS	-	24V	-	-
iLuminate AC to DC Constant Voltage Power Supply	DMX - DMX512 Enabled DALI - DALI-2 Enabled BLE - Bluetooth Enabled	24V - 24VDC	30W - 30W 60W - 60W 100W - 100W 200W - 100W x 2 300W - 100W x 3	JBOX - Dry/Damp Rated IP66 - Wet Rated

PROJECT NAME _____ FIXTURE TYPE _____ LOCATION _____