



INSTALLATION INSTRUCTIONS

WCC700 / WCC1400 THERMOSTAT KIT #629096848

SAFETY

 **WARNING:**

Before starting installation, read and understand all safety label and warnings on the machine. Also review and understand all safety instructions in the owners, installation and service manuals.

Failure to comply could result in serious injury, death or damage to the equipment.

QUALIFIED SERVICE PERSONNEL

 **WARNING:**

Only trained and certified electrical, plumbing and refrigeration technicians should service this unit.

All wiring and plumbing must conform to national and local codes. Failure to comply could result in serious injury, death or equipment damage.

SAFETY PRECAUTIONS

This unit has been specifically designed to provide protection against personal injury. To ensure continued protection observe the following:

 **WARNING:**

Disconnect power to the unit before servicing. Follow all lock out/tag out procedures established by the user. Verify all power is off to the unit before performing any work.

Failure to comply could result in serious injury, death or damage to the equipment.

 **CAUTION:**

Always be sure to keep area around the unit clean and free of clutter

Failure to keep this area clean may result in injury or equipment damage.



INSTALLATION

1. Open kit and remove new parts.
2. Seal the small non-flared end of the thermostat with 1/4 to 1/2 in. of food-grade silicone. Let it set for 15 to 30 minutes.
3. Remove panels, as needed.
4. Gently pull gray sensing bulb from current thermostat well and remove thermostat well.
5. Loosen the clamp under dispense tray assembly with ¼ nut driver.
6. Rotate dispense tray assembly 90 degrees.
7. Separate drop tube from dispense tray assembly.
8. Remove black foam insulation from old drop tube assembly and place it on the new drop tube.
9. Insert new drop tube assembly into the ice machine and dispense assembly and rotate it 90 degrees to the original position.
10. Tighten the dispense tray clamp.
11. Place the new thermostat well into dispense tray assembly and gently insert sensing bulb down into thermostat well until it touches the bottom of tube, where silicone was applied.
12. Apply a small amount of silicone in the flare opening of thermostat tube.
13. Attach all panels, turn the unit on, and follow standard start up procedures.