

CUSTOMER NAME _____
 STORE # _____
 ADDRESS _____
 CITY, ST., ZIP _____
 PHONE _____
 MODEL# & SERIAL # _____

SCHEDULED MAINTENANCE CHECK LIST F C B V3

- 1. Replace O-Rings and nylon sleeve in each barrel. P.M. Kit P/N 1040
- 2. Check the Stainless Steel retainer, replace if necessary.
- 3. Check the following and replace if necessary:
 - Scraper blades
 - Beater body
 - Face plate O-Ring
 - Spinner
 - Sensor
- 4. Dispensing Valve
 - Check caged O-Ring and replace if necessary
 - Lube caged O-Ring
 - Adjust return spring tension
- 5. Check for and repair leaks on the following:
 - CO₂
 - Water
 - Syrup
- 6. Test and repair if necessary
 - CO₂ pressure switch
 - Water pressure switch
 - Syrup Sold-Out systems
- 7. Set all CO₂ pressure settings
- 8. Brix all products
- 9. Check running water pressure
- 10. Set beater motor current adjustment – 150 ±2
- 11. Check the following, reset if necessary
 - All 10 DIP switch setting
 - Time clock
 - Sleep time
 - Viscosity settings
 - Voltage
 - Refrigerant type
 - Defrost times
 - Wake time
 - Sensors
 - Beater motor manufacturer
- 12. Clean unit as needed
- 13. Clean CONDENSER
- 14. Sanitize unit
- 15. Restart unit, adjust product viscosity