

Builders
CHOICE[®]

SPOKANE

WOOD DOORS
IN STOCK COLLECTION





04	EXTERIOR DOOR COLLECTION
08	INTERIOR DOOR COLLECTION
16	FIRE-RATED COLLECTION
18	BARN DOOR COLLECTION
20	CARE & FINISHING / WARRANTY



OUR HISTORY


OrePac is a family-owned and operated business, founded by the Hart family in 1977. Through strong leadership and a commitment to success, the company has grown into one of the premier distributors in the building industry.

Trust, integrity, and a dedication to excellence are the values most important to OrePac. That commitment can be found in the services we offer, the quality of the products we provide, and the way we treat our employees and customers. This dedication to our markets has enabled us to make a positive impact on the shelter industry and the communities we serve.

What to Know About Builders Choice Wood Doors

Easy Online Ordering with OrePac Marketplace

At OrePac, our goal is to Make Complicated Simple™. That's why we've created an industry-leading configurator to simplify the door ordering process for our dealers. Talk to your OrePac Sales Representative to find out more about this easy and time-saving tool.



Turn Your Door Style into a Versatile Pocket Door

The CS Cavity Slider™ is a practical solution for those areas where there is not enough space for a swinging door. In addition to its space saving attributes in restrooms, hallways and laundries, it can be used with confidence for architectural feature openings around your project. Contact your OrePac Sales Representative for more information.



Complete the Look with Builders Choice Moulding

We are proud to offer a wide selection of moulding and millwork to complete your home project. Whether you're building a new home, remodeling, or simply updating a room, Builders Choice offers millwork for all professional and DIY applications. Browse our moulding and millwork catalogs to find moulding in architectural profiles and wood species that complement any style of home.



Builders
HOICE

EXTERIOR DOOR COLLECTION



4501 | shown in knotty alder

CRAFTSMAN | KNOTTY ALDER



4033 | Flat



4701 SL



4182 | Raised



4612 SL



4662 | Flat



4662 SL



ATTRIBUTE KEY:

Ovolo Sticking Square Sticking Low-E Glass Clear Beveled Glass

OPTIONS KEY:

Available in 8'



FIR



4662 | Raised
☀️ 📐



4632 | Flat
📐



4633 | Flat
📐



4662 | Raised
📐



4663 | Raised
📐



TRADITIONAL | KNOTTY ALDER



4082 | Flat




4082 | Raised
 



4082V | Raised
 



4082A | Raised
 



4082VA | Raised


CONTEMPORARY | FIR



4055G | Flat


COUNTRY SASH & PRAIRIE MISSION | FIR



4144 | Raised




4944 | Raised


CLEAR FRENCH | KNOTTY ALDER

FIR



4501
  



4510
 



4701 SL
 



4501
 

ATTRIBUTE KEY:

 Ovolo Sticking  Square Sticking  Low-E Glass

OPTIONS KEY:

 Available in 8'

Builders
HOICE

INTERIOR DOOR COLLECTION

TRADITIONAL | KNOTTY ALDER



82 | Raised



82V | Raised



82A | Raised



82VA | Raised



82 | Flat



33 | Flat



30 | Flat



55 | Flat



ATTRIBUTE KEY:

Ovolo Sticking Square Sticking

Door thickness is 1-3/8" unless otherwise noted.



TRADITIONAL | FIR



20 | Flat
■



82 | Flat
■



33 | Flat
■



55 | Flat
■



82A | Raised
▤



44 | Raised
▤



66 | Raised
▤

ATTRIBUTE KEY:

▤ Ovolo Sticking ■ Square Sticking ▤ Cove Sticking

TRADITIONAL | PRIMED



20 | Flat
■



82 | Flat
■



30 | Flat
■



33 | Flat
■



55 | Flat
■

KNOTTY PINE



730 | Louver / Louver
■



82V | Raised
■



82VA | Raised
■



44 | Raised
■



66 | Raised
■

HEMLOCK



82 | Flat
■



33 | Flat
■



66 | Raised
■



44 | Raised
■




66 | Raised
■

CLEAR PINE



DECORATIVE FRENCH | PRIMED



1501 | Pantry (CURSIVE)




1501 | Satin Etch




1501 | Rain



CLEAR FRENCH | PRIMED



1501



1510



ATTRIBUTE KEY:

 Ovolo Sticking




1510 | shown in knotty alder

KNOTTY ALDER

FIR

CLEAR PINE



1501



1510



1510



1510

TRADITIONAL BIFOLDS | FIR



82 BF | Flat



33 BF | Flat



66 BF | Raised



KNOTTY ALDER



82 BF | Flat



33 BF | Flat



30 BF | Flat



55 BF | Flat



82 BF | Raised



KNOTTY PINE



82A BF | Raised



82VA BF | Raised



82V BF | Raised



82VA BF | Raised



66 BF | Raised



ATTRIBUTE KEY:

Ovolo Sticking Square Sticking Cove Sticking



82 BF | shown in primed

PRIMED



82 BF | Flat



33 BF | Flat



55 BF | Flat



Builders
HOICE

FIRE-RATED COLLECTION





4033F | shown in knotty alder

The doors on these pages are certified by an authorized testing agency and have a 20-minute fire rating.*

*To confirm fire door requirements in your jurisdiction, always check with your local building code.

TRADITIONAL | KNOTTY ALDER



4033F | Flat



4082F | Raised



4082AF | Raised



4082VAF | Raised



Builders
® CHOICE

BARN DOOR COLLECTION



BARN DOOR | KNOTTY ALDER



4020V
V-GROOVE



201-20
(REVERSIBLE)



BARN TRACK HARDWARE KIT

- Carbon steel construction
- Easy installation
- Handle included
- 86½" and 98½" sizes available



BLACK



SATIN NICKEL



4020V | shown in knotty alder

ATTRIBUTE KEY:

Square Sticking

OPTIONS KEY:

Available in 8'

Handling & Storage

1. Deliver doors in a clean truck and under cover.
2. Do not deliver or install doors until foundations, concrete floors, and plaster or texture walls are completely dry.
3. Allow doors time to acclimate to the conditions at the job site prior to installation.
4. Never subject doors to abnormal heat, dryness or humidity for prolonged periods (i.e. forced heat).
5. Store doors lying flat on a level surface above the ground in a dry, well-ventilated building and keep covered. Don't stack doors on end.
6. If the doors are to be stored on the job site, the entire door including top and bottom edges must be sealed with a clear or pigmented based sealer to prevent moisture absorption. All six sides of the door must be properly sealed including all edges of any cut openings (speak easy, mail slot, pet door, vent, peep site, etc.) for warranty to apply.
7. To keep doors protected, use clean gloves and equipment. Cover doors, but allow for air circulation. Carry, do not drag doors over any surface.

Important Note:

Panels of stile and rail doors are engineered to float so they can move with changes in climate without causing stress. Make sure these components are aligned before finishing. You can correct alignment by carefully moving the panel with a wood block, rubber mallet, and a soft touch. Components that have shifted and must be aligned are not considered "defects" according to the warranty.

Fitting & Hanging

1. When hanging a door, allow adequate clearance for swelling of door and frame in extremely damp weather.
2. Use designated sizes to avoid cutting door width. For trimming ends, we recommend a sharp, fine-tooth saw.
3. Be careful not to impair structural strength of door when fitting hardware or special features. To prevent distortion, set hinges in straight line. Use three hinges on doors 7' or less; four hinges on doors over 7' high. Jambs and stops must be square and plumb.
4. Protect outward swinging doors that are exposed to the elements. An adequate overhang is strongly recommended for exterior doors. A general rule of thumb for an overhang is to measure height from porch to overhang and divide the distance in half. That measurement would be a minimum overhang width recommended.
5. Immediately after fitting or cutting, and prior to weatherstripping and hanging any door, give the entire surface (including all edges) two coats of paint/stain, varnish or a quality sealer to prevent moisture absorption.

6. To minimize heat loss and reduce energy costs, use any good weatherstrip on exterior doors.
7. Damage incurred due to extreme temperature build-up when a storm door is used is not considered a defect.

Important Note:

OrePac reserves the right to make product improvement changes in specifications, materials and construction details.

Preparation & Finishing

1. Inspect door carefully for defects before finishing.
2. All wood doors supplied by OrePac require sanding and prep prior to finish. The amount of sanding will depend on the expected appearance after finish.
3. Remove all dust with a tack cloth before beginning to apply finish.
4. Hang the door prior to finishing, then remove to finish properly.
5. Apply finish to the door immediately after fitting and hanging, but never during or immediately after high periods of moisture.
6. The door should be finished while lying flat for maximum performance of finishing.
7. Use solvent-based paints, sealers and stains, or when applicable, high quality water-based paints or stains, and follow the paint/stain manufacturer's directions. Apply finish to all surfaces including top and bottom edges, and the edges of all cut openings (speak easy, mail slot, vent, pet door, peep site, etc.). Dark color finishes should not be used on doors exposed to prolonged direct sunlight. The heat buildup may cause warping, veneer checks or separation.
8. To stain the door: Apply a stain and sealer combination as recommended by the paint/stain manufacturer for the type of application (either exterior or interior). The stain or sealer combination will stain the door and seal the surface. Apply three coats of clear top coat, such as varnish or polyurethane. Sand lightly between coats. All exteriors must have ultra violet (UV) inhibitors in the finish. Do not use solid-based stains as the final finish. These finishes must have three coats of varnish or polyurethane as final top coat.
9. To paint the door: Use a quality solvent-based primer, followed by three coats of a good exterior paint recommended by the paint/stain manufacturer to be compatible with the primer. When finishing glazed doors, apply top coats generously to bridge wood and glass. To protect against moisture, lap paint onto glass 1/16 inch. For interior applications, use a quality interior primer followed by two coats of interior latex enamel or solvent-based paint. The door manufacturer and distributor are not responsible for the final appearance of doors finished in the field. It is expected that the contractor will make adjustments as needed to achieve the desired results.
10. All finishes will last longer when protected from the direct sun and rain by an overhang or porch. If the door is exposed to the elements, a fine bead of silicone caulk should be used between the glass and sticking or panel and sticking on the door's exterior.

OrePac warranties that each door purchased from OrePac is of good material and workmanship and shall be free of defects which render such door(s) unserviceable or unfit for ordinary recommended use.

One-Year Exterior Door Warranty


Doors used in an exterior application (with controlled climate conditions on one side) shall carry a one-year limited warranty from the date of purchase from the dealer. This warranty applies only to doors that have been properly finished, sealed, and hung in a location protected from direct exposure to sun and rain, under normal conditions. For more details please refer to the Wood Door Installation Guide.

Five-Year Interior Door Warranty

Doors used in an interior application (with controlled climate conditions on both sides) shall carry a five-year limited warranty from the date of purchase from the dealer. This warranty applies only to doors that have been properly finished, sealed, and hung. The five-year warranty applies only to the original homeowner and is not transferable.

Determining Adequate Overhang

To determine if your door has adequate overhang, measure up from the bottom of the door to the ceiling and divide that distance by two. The resulting number will be the minimum allowable overhang. If you have a western or southern exposure, you may still receive direct sunlight on the door and a larger overhang will be required.



Characteristics Excluded from Warranties

The following are not defects in the workmanship or material and are not covered by this written warranty:

1. Damage caused by failure to comply with the "Care & Finishing" instructions.
 2. Warp of less than or equal to 1/4" in the plane of any door 3' x 7' or smaller.
 3. Defect caused by a warped or bowed jamb/frame unit or improper installation.
 4. Natural variations in the color or texture of the wood.
 5. Failure to properly seal and maintain the integrity of the door finish. All six sides, and the edges of any cut openings (speak easy, mail slot, pet door, vent, peep site, etc.) must be sealed immediately after fitting and hanging.
 6. Panel misalignment or shrinkage.
 7. Rail expansion due to climate conditions.
 8. Damage caused by extreme temperature build-up where a storm door is utilized.
 9. Failure to perform normal homeowner's maintenance, including but not limited to, reapplying topcoat on a yearly basis.
 10. The performance or appearance of finishes applied.
-

Limitation of Liability

The liability of OrePac is expressly limited to the replacement or repair of the door or a refund, in full, of the original purchase price. OrePac shall not be liable for any special, consequential indirect or incidental damages based upon breach of express or implied warranty, breach of contract, negligence, strict tort or any loss of profits, loss of savings or revenue, loss of use of the door or structure in which the door is installed, cost of any substitute doors, claims by third parties including subsequent purchasers of OrePac's products and injury to property.

This warranty gives you specific legal rights and you may have other rights which vary from state to state.

Additional warranty details and restrictions are available through your OrePac representative.

Builders ® CHOICE



WARNING: Cancer and Reproductive Harm
www.P65warnings.ca.gov

OrePac Building Products
www.orepac.com



©2023 OrePac Building Products. All rights reserved. OP-SP_0623

OrePac Spokane

15120 E Euclid
Spokane, WA 99216

T: 509-892-5555

F: 509-892-5550

