

# RENOLIT ALKORPLAN<sup>81038</sup>

## PVC seam sealer

Solution of flexible polyvinyl chloride (PVC-P) in tetrahydrofuran (THF)



### CHARACTERISTICS

Appearance	Volatile, mobile liquid		
Odour	Ethereal		
Consistency	Viscous, 1200 mPa.s at 20°C		
Colours	White (90300)	Charcoal (79851)	Copper green (60884)
	Light grey (71004)	Grey (73321)	Terracotta (82119)

### TECHNICAL PROPERTIES

Flash point		-17°C
Boiling point/range		65 - 66°C
Flammability (solid/gas)	Upper explosion limit:	12 % (V)
	Lower explosion limit:	1.5 % (V)







### FIELD OF APPLICATION

- Reinforcement of welded joints, T borders and corners for **RENOLIT ALKORPLAN** waterproofing membranes.

### INSTRUCTIONS FOR USE

- Shake well before use.
- Dilute only with THF.
- Consumption: approximately 10g/lm
- See **RENOLIT ALKORPLAN** installation instructions.

### PACKAGING

Type	Colour	Packaging	Content	Unit
81038-030	White (90300)	1L	Can	6 pces/box LQ 
81038-004	Light grey (71004)	1L	Can	6 pces/box LQ 
81038-006	Charcoal (79851)	1L	Can	6 pces/box LQ 
81038-024	Grey (73321)	1L	Can	6 pces/box LQ 
81038-010	Copper green (60884)	1L	Can	6 pces/box LQ 
81038-011	Terracotta (82119)	1L	Can	6 pces/box LQ 

### STORAGE

- Store in dry unheated places, in original packaging. Protect from sun and frost. Shelf life: at least 12 months.
- Ventilate well during and after application.
- Regulations concerning flammable liquids must be observed.
- Do not empty into drains. Take precautionary measures against static discharges.
- Refer to the text on the label and take into consideration the data given on the material safety data sheet, which is available on request.

### TRANSPORT

Proper shipping name: ADHESIVES (CONTAINS TETRAHYDROFURANE)  
IMDG/IATA/ADR: Flammable liquids; Class 3 PKg Gr II; ONU Nr 1133

[WWW.RENOLIT.ALKORPLAN.COM](http://WWW.RENOLIT.ALKORPLAN.COM)

RENOLIT UK Ltd, Station Road - Cramlington, Northumberland NE23 8AQ - United Kingdom  
T +44 1670 718283 - F +44 1670 719367 - [renolit.cramlington@renolit.com](mailto:renolit.cramlington@renolit.com)

RENOLIT Belgium N.V. - Export Dpt. - Industriepark De Bruwaan 43 - 9700 Oudenaarde - Belgium  
T +32 (0)55 33 98 51 - F +32 (0)55 31 86 58 - [renolit.belgium@renolit.com](mailto:renolit.belgium@renolit.com)



Rely on it.