


RENOLIT ALKORPLUS₈₁₀₅₇

Double-sided butyl adhesive tape



PRODUCT DESCRIPTION

Double-sided butyl adhesive tape consisting of a butyl rubber adhesive compound and a peelable liner.

CHARACTERISTICS

	VALUE	TEST
Solids	100 %	-
180° Peel Adhesion	20 N/cm	ASTM D 1000
180° Peel Adhesion @ 5°C on concrete	17 N/cm	-
Probe Tack	8.0 N	ASTM D 2979
Vertical Flow	0 mm	ISO 7390
Application Temperature Range	0 °C / + 40 °C	-
Service Temperature Range	- 30 °C / + 90 °C	-
Total Volatile Organic Compound emissions (TVOC)	30 µg/m ³	ISO 16000-6

FIELD OF APPLICATION

The **RENOLIT ALKORPLUS₈₁₀₅₇** seam tape is used for jointing **RENOLIT ALKORPLUS** polyethylene vapour control layer overlaps and creating an airtight seal at parapets and around roof penetrations.

INSTRUCTIONS FOR USE

SURFACE PREPARATION

- The surface shall be clean, dry and free from debris, solvent and other surface contamination.

USE

For more detailed information regarding correct installation and use please refer to the **RENOLIT** installation instructions.

- Apply the tape onto the surface.
- Press down firmly using a roller or a cloth pad.
- Remove the peelable liner and apply the second surface while avoiding air bubbles.
- Immediately press down firmly using a roller or a cloth pad in order to create an airtight seal.

PACKAGING

Type	Width	Weight	Roll length	Packaging unit
81057	15 mm	0,100 kg	25 m	16 rolls / box

STORAGE

- Minimum 12 months in original unopened packaging and protected from humidity.
- Store in a well ventilated room and at a maximum temperature of 30°C (storage above 30°C may lead to difficulties to remove the liner when applying).

WWW.RENOLIT.COM/ROOFING

RENOLIT UK Station Road - Cramlington, Northumberland NE23 8AQ - United Kingdom
T +44 1670 718283 - F +44 1670 590096 - matthew.adamson@renolit.com

RENOLIT Belgium N.V. - Export Dpt. - Industriepark De Bruwaan 43 - 9700 Oudenaarde - Belgium
T +32 (0)55 33 98 51 - F +32 (0)55 31 86 58 - renolit.belgium@renolit.com



Rely on it.