


# RENOLIT ALKORPLAN A Classic

## Adhered system



SQUAD.BE

### Product information

**RENOLIT ALKORPLAN A Classic**  
Laminated fleece-backed membrane of flexible PVC with woven polyester reinforcement.

### Application

**RENOLIT ALKORPLAN A Classic** is used as a waterproofing membrane within fully bonded systems with the **RENOLIT ALKORPLUS<sub>81068</sub>** PU glue or the universal **RENOLIT ALKORPLUS Dualfix<sub>81065</sub>** glue.

### Certificates

Product certification EN 13956  
0479-CPR-BC2-320-01452-0001-01

Certificates available on our website  
[www.renolit.alkorplan.com](http://www.renolit.alkorplan.com)

### PRODUCT DATA

	Method	Production values RENOLIT ALKORPLAN A Classic				Unit
		1.2 mm	1.5 mm	1.8 mm	2.0 mm	
Tensile strength	EN 12311-2 (A)	≥ 1050	≥ 1100	≥ 1125	≥ 1150	N/50 mm
Elongation	EN 12311-2 (A)	≥ 15	≥ 16			%
Dimensional stability (6h at 80 °C)	EN 1107-2	≤  0.3				%
Cold crack temperature	EN 495-5	≤ -25				°C
Nail tear resistance	EN 12310-1	≥ 550	≥ 625	≥ 700	≥ 775	N
Tear resistance	EN 12310-2	≥ 325	≥ 350	≥ 375	≥ 400	N
Joint peel resistance	EN 12316-2	BOJ or ≥ 200    ≥ 225    ≥ 250    ≥ 275				N/50 mm
Water vapour diffusion resistance (μ)	EN 1931	20000				-
Resistance to static perforation	EN 12730	≥ 20				kg
Reaction to fire	EN 13501-1	E				-

### PACKAGING

	Colour	Thickness	Width	Weight	Roll length	Roll weight
RENOLIT ALKORPLAN A <sub>35F79</sub>	Light grey (71004)	1.2 mm (3.2 mm incl. fleece)	2.10 m	1.80 kg/m <sup>2</sup>	15 lm	ca. 60 kg
	Light grey (71004)	1.5 mm (3.5 mm incl. fleece)	2.10 m	2.15 kg/m <sup>2</sup>	15 lm	ca. 74 kg
	Light grey (71004)	1.8 mm (3.8 mm incl. fleece)	2.10 m	2.50 kg/m <sup>2</sup>	15 lm	ca. 83 kg
	Light grey (71004)	2.0 mm (4.0 mm incl. fleece)	2.10 m	2.80 kg/m <sup>2</sup>	15 lm	ca. 92 kg

### Storage

The rolls should be stored horizontally and parallel to each other. Store in the original packaging, in a dry and frost-free area, protected from direct sunlight. The maximum stack height in the original packaging is 5 open crates.

The **RENOLIT ALKORPLAN** roofing membranes are supplied in rolls on cardboard cores. Every delivery may contain up to 10% of short rolls (minimum length: 8 m).

*This document replaces and supersedes all prior versions.*

## WWW.RENOLIT.ALKORPLAN.COM

RENOLIT UK Ltd, Station Road - Cramlington, Northumberland NE23 8AQ - United Kingdom  
T +44 1670 718283 - F +44 1670 719367 - [renolit.cramlington@renolit.com](mailto:renolit.cramlington@renolit.com)

RENOLIT Belgium N.V. - Export Dpt. - Industriepark De Bruwaan 43 - 9700 Oudenaarde - Belgium  
T +32 (0)55 33 98 51 - F +32 (0)55 31 86 58 - [renolit.belgium@renolit.com](mailto:renolit.belgium@renolit.com)



Rely on it.

R2F79DX0823