



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



RENOLIT ALKORPLUS PU ADHESIVE 81065200 DUALFIX

Date of compilation: 16/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** RENOLIT ALKORPLUS
PU ADHESIVE
81065200 DUALFIX
- Other means of identification:**
Non-applicable
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Multiuse adhesive. For professional users only.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Archityne Limited
1/36 Devon St
Bucklands Beach,
Auckland 2012
- 1.4 Emergency telephone number:** 0800 764 766 – National Poisons Centre

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Carc. 2: Carcinogenicity, Category 2, H351
Eye Irrit. 2: Eye irritation, Category 2, H319
Press. Gas: Liquefied gases under pressure, H280
Resp. Sens. 1: Sensitisation, respiratory, Category 1, H334
Skin Irrit. 2: Skin irritation, Category 2, H315
Skin Sens. 1: Sensitisation, skin, Category 1, H317
STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2, H373
STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Danger
-
- Hazard statements:**
Carc. 2: H351 - Suspected of causing cancer.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Press. Gas: H280 - Contains gas under pressure, may explode if heated.
Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
STOT SE 3: H335 - May cause respiratory irritation.
- Precautionary statements:**
P201: Obtain special instructions before use.
P260: Do not breathe spray.
P264: Wash thoroughly after handling.
P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.
P304+P312: IF INHALED: Call a POISON CENTER/doctor if you feel unwell.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308+P313: IF exposed or concerned: Get medical advice/attention.

- CONTINUED ON NEXT PAGE -

Date of compilation: 16/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

Page 1/15

Document generated with Chemeter (www.siam-it.com)



Rely on it.

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

**RENOLIT ALKORPLUS
PU ADHESIVE
81065200 DUALFIX**

Date of compilation: 16/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

SECTION 2: HAZARDS IDENTIFICATION (continued)**Supplementary information:**

EUH204: Contains isocyanates. May produce an allergic reaction.

Additional Labelling:

As from 24 August 2023 adequate training is required before industrial or professional use.

UFI: KQ00-X0T3-X002-3V9T

2.3 HSNO Classifications:

6.7B, 6.4A, 6.5A, 6.3A, 6.5B, 6.9B,

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.1 Substance:**

Non-applicable

3.2 Mixture:**Chemical description:** Mixture composed of polymers and resins in solvent**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 53862-89-8 EC: Non-applicable Index: Non-applicable REACH:Non-applicable	Isocyanic acid, polymethylenepolyphenylene ester, polymer with .alpha.-hydro.-omega.-hydroxypoly(oxy(methyl-1,2-ethanediyl)) ¹ Regulation 1272/2008 Acute Tox. 4: H332; Eye Irrit. 2: H319; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT RE 2: H373; STOT SE 3: H335 - Danger Self-classified	40 - <60 %
CAS: 9016-87-9 EC: 618-498-9 Index: Non-applicable REACH:Non-applicable	4,4'-methylenediphenyl diisocyanate, isomers and homologues ¹ Regulation 1272/2008 Acute Tox. 4: H332; Carc. 2: H354; Eye Irrit. 2: H319; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT RE 2: H373; STOT SE 3: H335 - Danger Self-classified	15 - <25 %
CAS: 29118-24-9 EC: Non-applicable Index: Non-applicable REACH:Non-applicable	(1E)-1H,2H-Perfluoroprop-1-ene ² Regulation 1272/2008 Press. Gas: H280 - Warning Self-classified	15 - <25 %
CAS: 101-68-8 EC: 202-966-0 Index: 615-005-00-9 REACH:01-2119457014-47-XXXX	4,4'-methylenediphenyl diisocyanate ¹ Regulation 1272/2008 Acute Tox. 4: H332; Carc. 2: H351; Eye Irrit. 2: H319; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT RE 2: H373; STOT SE 3: H335 - Danger ATP-CLP00	5 - <10 %
CAS: 13674-84-5 EC: 237-158-7 Index: Non-applicable REACH:01-2119480419-30-XXXX	Tris(1-chloro-2-propyl) Phosphate ¹ Regulation 1272/2008 Acute Tox. 4: H302+H312+H332 - Warning Self-classified	5 - <10 %

¹ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878² Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	Specific concentration limit
4,4'-methylenediphenyl diisocyanate, isomers and homologues CAS: 9016-87-9 EC: 618-498-9	% (w/w) >=5: Skin Irrit. 2 - H315 % (w/w) >=5: Eye Irrit. 2 - H319 % (w/w) >=0,1: Resp. Sens. 1 - H334 % (w/w) >=5: STOT SE 3 - H335
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	% (w/w) >=5: Skin Irrit. 2 - H315 % (w/w) >=5: Eye Irrit. 2 - H319 % (w/w) >=0,1: Resp. Sens. 1 - H334 % (w/w) >=5: STOT SE 3 - H335

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

- CONTINUED ON NEXT PAGE -

Date of compilation: 16/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

Page 2/15



**RENOLIT ALKORPLUS
PU ADHESIVE
81065200 DUALFIX**

Date of compilation: 16/07/2020 Revised: 05/08/2022 Version: 3 (Replaced 2)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	Non-applicable	Non-applicable	
	Non-applicable	Non-applicable	
	11 mg/L (ATEi)		
Isocyanic acid, polymethylenepolyphenylene ester, polymer with .alpha.-hydro.-omega.-hydroxypoly(oxy(methyl-1,2-ethanediy)) CAS: 53862-89-8 EC: Non-applicable	Non-applicable	Non-applicable	
	Non-applicable	Non-applicable	
	11 mg/L (ATEi)		
4,4'-methylenediphenyl diisocyanate, isomers and homologues CAS: 9016-87-9 EC: 618-498-9	Non-applicable	Non-applicable	
	Non-applicable	Non-applicable	
	11 mg/L (ATEi)		

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

- CONTINUED ON NEXT PAGE -



**RENOLIT ALKORPLUS
PU ADHESIVE
81065200 DUALFIX**



Date of compilation: 16/07/2020 Revised: 05/08/2022 Version: 3 (Replaced 2)

SECTION 5: FIREFIGHTING MEASURES (continued)

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum time: 18 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

- CONTINUED ON NEXT PAGE -



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



**RENOLIT ALKORPLUS
PU ADHESIVE
81065200 DUALFIX**

Date of compilation: 16/07/2020 Revised: 05/08/2022 Version: 3 (Replaced 2)

SECTION 7: HANDLING AND STORAGE (continued)

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Workplace Exposure Standards – New Zealand:

Source	Substance	Cas No.	TWA	STEL	Notes
New Zealand Workplace Exposure Standards (WES)	Methylene bisphenyl isocyanate, as -NCO	101-68-8	0.02 mg/m3	0.07 mg/m3	dscn: Dermal sensitiser, rscn: Respiratory sensitiser, ifv: Inhalable fraction and vapour,.

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
4,4'-methylenediphenyl diisocyanate, isomers and homologues CAS: 9016-87-9 EC: 618-498-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	0,05 mg/m³	Non-applicable	0,025 mg/m³
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	0,05 mg/m³	Non-applicable	0,025 mg/m³

PNEC:

Identification				
4,4'-methylenediphenyl diisocyanate, isomers and homologues CAS: 9016-87-9 EC: 618-498-9	STP	1 mg/L	Fresh water	1 mg/L
	Soil	1 mg/kg	Marine water	0,1 mg/L
	Intermittent	10 mg/L	Sediment (Fresh water)	Non-applicable
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	STP	1 mg/L	Fresh water	1 mg/L
	Soil	1 mg/kg	Marine water	0,1 mg/L
	Intermittent	10 mg/L	Sediment (Fresh water)	Non-applicable
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

- CONTINUED ON NEXT PAGE -





**RENOLIT ALKORPLUS
PU ADHESIVE
81065200 DUALFIX**

Date of compilation: 16/07/2020



Revised: 05/08/2022

Version: 3 (Replaced 2)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands




Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.4 mm)		EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield		EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties		EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties		EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	0 % weight
V.O.C. density at 25 °C:	0 kg/m ³ (0 g/L)
Average carbon number:	Non-applicable
Average molecular weight:	Non-applicable

- CONTINUED ON NEXT PAGE -



**RENOLIT ALKORPLUS
PU ADHESIVE
81065200 DUALFIX**

Date of compilation: 16/07/2020 Revised: 05/08/2022 Version: 3 (Replaced 2)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Fluid
Colour:	 Blue
Odour:	Not available
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	Non-applicable *
Vapour pressure at 25 °C:	Non-applicable *
Vapour pressure at 50 °C:	0 Pa (0 kPa)
Evaporation rate at 25 °C:	Non-applicable *

Product description:

Density at 25 °C:	Non-applicable *
Relative density at 25 °C:	1,1
Dynamic viscosity at 25 °C:	Non-applicable *
Kinematic viscosity at 25 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 25 °C:	Non-applicable *
Partition coefficient n-octanol/water 25 °C:	Non-applicable *
Solubility in water at 25 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *

Flammability:

Flash Point:	Non Flammable (>60 °C)
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	Non-applicable *
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *

Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



**RENOLIT ALKORPLUS
PU ADHESIVE
81065200 DUALFIX**

Date of compilation: 16/07/2020 Revised: 05/08/2022 Version: 3 (Replaced 2)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Other safety characteristics:

Surface tension at 25 °C: Non-applicable *

Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Danger of explosion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Not applicable	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- CONTINUED ON NEXT PAGE -



**RENOLIT ALKORPLUS
PU ADHESIVE
81065200 DUALFIX**

Date of compilation: 16/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.
- IARC: 4,4'-methylenediphenyl diisocyanate, isomers and homologues (3); 4,4'-methylenediphenyl diisocyanate (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Prolonged exposure can result in specific respiratory hypersensitivity.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	LD50 oral	7616 mg/kg	Rat
	LD50 dermal	10000 mg/kg	Rabbit
	LC50 inhalation	11 mg/L (ATEi)	
Tris(1-chloro-2-propyl) Phosphate CAS: 13674-84-5 EC: 237-158-7	LD50 oral	930 mg/kg	Rat
	LD50 dermal	2000 mg/kg	Rabbit
	LC50 inhalation	11 mg/L (4 h)	Rat
Isocyanic acid, polymethylenepolyphenylene ester, polymer with .alpha.-hydro-.omega.-hydroxypoly(oxy(methyl-1,2-ethanediyl)) CAS: 53862-89-8 EC: Non-applicable	LD50 oral	Non-applicable	
	LD50 dermal	Non-applicable	
	LC50 inhalation	11 mg/L (ATEi)	
4,4'-methylenediphenyl diisocyanate, isomers and homologues CAS: 9016-87-9 EC: 618-498-9	LD50 oral	Non-applicable	
	LD50 dermal	Non-applicable	
	LC50 inhalation	11 mg/L (ATEi)	

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Toxicity:

- CONTINUED ON NEXT PAGE -



**RENOLIT ALKORPLUS
PU ADHESIVE
81065200 DUALFIX**

Date of compilation: 16/07/2020 Revised: 05/08/2022 Version: 3 (Replaced 2)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Acute toxicity:

Identification	Concentration	Species	Genus
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	LC50	1000 mg/L (96 h)	Brachydanio rerio
	EC50	Non-applicable	
	EC50	Non-applicable	
Tris(1-chloro-2-propyl) Phosphate CAS: 13674-84-5 EC: 237-158-7	LC50	56,2 mg/L (96 h)	Brachydanio rerio
	EC50	131 mg/L (48 h)	Daphnia magna
	EC50	45 mg/L (72 h)	Scenedesmus subspicatus

Chronic toxicity:

Identification	Concentration	Species	Genus
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	NOEC	Non-applicable	
	NOEC	10 mg/L	Daphnia magna

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
	Tris(1-chloro-2-propyl) Phosphate CAS: 13674-84-5 EC: 237-158-7	BOD5	Non-applicable	Concentration
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	0 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	BCF	150
	Pow Log	4.51
	Potential	High
Tris(1-chloro-2-propyl) Phosphate CAS: 13674-84-5 EC: 237-158-7	BCF	5
	Pow Log	2.59
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	Koc	Non-applicable	Henry	Non-applicable
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	2,068E-2 N/m (203,45 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

- CONTINUED ON NEXT PAGE -



**RENOLIT ALKORPLUS
PU ADHESIVE
81065200 DUALFIX**

Date of compilation: 16/07/2020 Revised: 05/08/2022 Version: 3 (Replaced 2)

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP7 Carcinogenic, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to NZS 5433:2021, ADR 2023 and RID 2023:



- 14.1 UN number or ID number:** UN3500
14.2 UN proper shipping name: CHEMICAL UNDER PRESSURE, N.O.S. ((1E)-1H,2H-Perfluoroprop-1-ene)
14.3 Transport hazard class(es): 2
Labels: 2.2
14.4 Packing group: N/A
14.5 Environmental hazards:
 No
14.6 Special precautions for user
 Special regulations: 274, 659
 Tunnel restriction code: C/E
 Physico-Chemical properties: see section 9
 Limited quantities: 0
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 40-20:



- 14.1 UN number or ID number:** UN3500
14.2 UN proper shipping name: CHEMICAL UNDER PRESSURE, N.O.S. ((1E)-1H,2H-Perfluoroprop-1-ene)
14.3 Transport hazard class(es): 2
Labels: 2.2
14.4 Packing group: N/A
14.5 Marine pollutant:
 No
14.6 Special precautions for user
 Special regulations: 274, 362
 EmS Codes: F-C, S-V
 Physico-Chemical properties: see section 9
 Limited quantities: 0 Segregation group: Non-applicable
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2023:

- CONTINUED ON NEXT PAGE -



**RENOLIT ALKORPLUS
PU ADHESIVE
81065200 DUALFIX**

Date of compilation: 16/07/2020 Revised: 05/08/2022 Version: 3 (Replaced 2)

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number or ID number:** UN3500
14.2 UN proper shipping name: CHEMICAL UNDER PRESSURE, N.O.S. ((1E)-1H,2H-Perfluoroprop-1-ene)
14.3 Transport hazard class(es): 2
 Labels: 2.2
14.4 Packing group: N/A
14.5 Environmental hazards:
 No
14.6 Special precautions for user
 Physico-Chemical properties: see section 9
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

15.1 HSNO Approval:

HSR Number	Group Standard
HSR002520	Aerosols (Non-flammable, Carcinogenic) Group Standard 2020

Applicable Legislation:

- Hazardous Substances and New Organisms Act 1996 (HSNO)
- Health and Safety at Work (Hazardous Substances) Regulations 2017
- NZS 5433 (Transport of Dangerous Goods by Land)

- CONTINUED ON NEXT PAGE -



Rely on it.

Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



RENOLIT ALKORPLUS PU ADHESIVE 81065200 DUALFIX

Date of compilation: 16/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

SECTION 15: REGULATORY INFORMATION (continued)

Contains more than 0.1 % of 4,4'-methylenediphenyl diisocyanate, isomers and homologues, 4,4'-methylenediphenyl diisocyanate by weight. 1. Shall not be used as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 August 2023, unless:

(a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the employer or self-employed ensures that industrial or professional user(s) have successfully completed training on the safe use of diisocyanates prior to the use of the substance(s) or mixture(s).

2. Shall not be placed on the market as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 February 2022, unless:

(a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the supplier ensures that the recipient of the substance(s) or mixture(s) is provided with information on the requirements referred to in point (b) of paragraph 1 and the following statement is placed on the packaging, in a manner that is visibly distinct from the rest of the label information: "As from 24 August 2023 adequate training is required before industrial or professional use".

3. For the purpose of this entry "industrial and professional user(s)" means any worker or self-employed worker handling diisocyanates on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) or supervising these tasks.

4. The training referred to in point (b) of paragraph 1 shall include the instructions for the control of dermal and inhalation exposure to diisocyanates at the workplace without prejudice to any national occupational exposure limit value or other appropriate risk management measures at national level. Such training shall be conducted by an expert on occupational safety and health with competence acquired by relevant vocational training. That training shall cover as a minimum:

(a) the training elements in point (a) of paragraph 5 for all industrial and professional use(s).

(b) the training elements in points (a) and (b) of paragraph 5 for the following uses:

— handling open mixtures at ambient temperature (including foam tunnels)

— spraying in a ventilated booth

— application by roller —

application by brush

— application by dipping and pouring

— mechanical post treatment (e.g. cutting) of not fully cured articles which are not warm anymore

— cleaning and waste

— any other uses with similar exposure through the dermal and/or inhalation route

(c) the training elements in points (a), (b) and (c) of paragraph 5 for the following uses:

— handling incompletely cured articles (e.g. freshly cured, still warm)

— foundry applications

— maintenance and repair that needs access to equipment

— open handling of warm or hot formulations (> 45 °C)

— spraying in open air, with limited or only natural ventilation (includes large industry working halls) and spraying with high energy (e.g. foams, elastomers)

— and any other uses with similar exposure through the dermal and/or inhalation route.

5. Training elements:

(a) general training, including on-line training, on:

— chemistry of diisocyanates

— toxicity hazards (including acute toxicity)

— exposure to diisocyanates

— occupational exposure limit values

— how sensitisation can develop —

odour as indication of hazard —

importance of volatility for risk

— viscosity, temperature, and molecular weight of diisocyanates

— personal hygiene

— personal protective equipment needed, including practical instructions for its correct use and its limitations

— risk of dermal contact and inhalation exposure

— risk in relation to application process used

— skin and inhalation protection scheme

— ventilation

— cleaning, leakages, maintenance

— discarding empty packaging

— protection of bystanders

— identification of critical handling stages

— specific national code systems (if applicable)

— behaviour-based safety

— certification or documented proof that training has been successfully completed

(b) intermediate level training, including on-line training, on:

— additional behaviour-based aspects

— maintenance

- CONTINUED ON NEXT PAGE -

Date of compilation: 16/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

Page 13/15



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



RENOLIT ALKORPLUS PU ADHESIVE 81065200 DUALFIX

Date of compilation: 16/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

SECTION 15: REGULATORY INFORMATION (continued)

- management of change
 - evaluation of existing safety instructions
 - risk in relation to application process used
 - certification or documented proof that training has been successfully completed
 - (c) advanced training, including on-line training, on:
 - any additional certification needed for the specific uses covered
 - spraying outside a spraying booth
 - open handling of hot or warm formulations (> 45 °C)
 - certification or documented proof that training has been successfully completed
6. The training shall comply with the provisions set by the Member State in which the industrial or professional user(s) operate. Member States may implement or continue to apply their own national requirements for the use of the substance(s) or mixture(s), as long as the minimum requirements set out in paragraphs 4 and 5 are met.
7. The supplier referred to in point (b) of paragraph 2 shall ensure that the recipient is provided with training material and courses pursuant to paragraphs 4 and 5 in the official language(s) of the Member State(s) where the substance(s) or mixture(s) are supplied. The training shall take into consideration the specificity of the products supplied, including composition, packaging, and design.
8. The employer or self-employed shall document the successful completion of the training referred to in paragraphs 4 and 5. The training shall be renewed at least every five years.
9. Member States shall include in their reports pursuant to Article 117(1) the following information:
- (a) any established training requirements and other risk management measures related to the industrial and professional uses of diisocyanates foreseen in national law
 - (b) the number of cases of reported and recognised occupational asthma and occupational respiratory and dermal diseases in relation to diisocyanates
 - (c) national exposure limits for diisocyanates, if there are any
 - (d) information about enforcement activities related to this restriction.
10. This restriction shall apply without prejudice to other Union legislation on the protection of safety and health of workers at the workplace.
- Contains more than 0.1 % of 4,4'-methylenediphenyl diisocyanate, 4,4'-methylenediphenyl diisocyanate, isomers and homologues by weight. This product may not be distributed in its present form for first-time sale to the general public after 27th December 2010 unless the packaging contains protective gloves meeting the provisions of Regulation (EU) 2016/425.
- Shall not be used in:
- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, —tricks and jokes,
 - games for one or more participants, or any article intended to be used as such, even with ornamental aspects.
- Specific provisions in terms of protecting people or the environment:**
- It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.
- Other legislation:**
- The product could be affected by sectorial legislation
- 15.2 Chemical safety assessment:**
- The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

Texts of the legislative phrases mentioned in section 2:

- CONTINUED ON NEXT PAGE -

Date of compilation: 16/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

Page 14/15



Safety data sheet

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation



RENOLIT ALKORPLUS PU ADHESIVE 81065200 DUALFIX

Date of compilation: 16/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

SECTION 16: OTHER INFORMATION (continued)

H280: Contains gas under pressure, may explode if heated.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317: May cause an allergic skin reaction.
H351: Suspected of causing cancer.
H335: May cause respiratory irritation.
H373: May cause damage to organs through prolonged or repeated exposure.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled.
Acute Tox. 4: H332 - Harmful if inhaled.
Carc. 2: H351 - Suspected of causing cancer.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Press. Gas: H280 - Contains gas under pressure, may explode if heated.
Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Inhalation).
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
STOT SE 3: H335 - May cause respiratory irritation.

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -

Date of compilation: 16/07/2020

Revised: 05/08/2022

Version: 3 (Replaced 2)

Page 15/15

Document generated with Chemeter (www.siam-it.com)