

N°: TERRAGUM E VV NH 001 EN

1. Identification code TERRAGUM E VV
2. Intended use Reinforced bitumen sheets for roof waterproofing
3. Manufacturer IKO-AXTER
6, rue Laferrière
75009 Paris
France
www.axter.eu/dop
4. Authorised representative NA
5. System of assessment and verification of constancy of performance of the product System 2+
- 6a. Product covered by the harmonised standard: EN 13707
The CSTB, notify body n° 0679 has performed under system 2+ the initial inspection of factory production control the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control n° 0679 - CPR - 0128.
- 6b. European Technical Assessment : NA
7. Declared performance

Essential characteristics			Performance				Harmonised technical specifications
			Value	Tolerance		Units	
				Min	Max		
Resistance to tearing (nail shank)	Longitudinal direction		NA	-	-	N	EN 13707:2014
	Cross direction		NA	-	-		
Tensile properties : maximum tensile force	Longitudinal direction		400	250	-	N/50mm	
	Cross direction		250	120	-		
Tensile properties : maximum elongation	Longitudinal direction		4	2	-	%	
	Cross direction		4	2	-		
Shear resistance of joint	Maximum force	Selvedge	NA	-	-	N/50mm	
		End joint	NA	-	-		
Peel resistance of joint	Maximum force	Selvedge	NA	-	-	N/50mm	
		End joint	NA	-	-		
Flexibility at low temperature			≤ -5			°C	
Durability EN 1296	Flow resistance at elevated temperature		NA	-	-	°C	
Durability EN 1297	Visible defects		NA				
Resistance to static loading (method A)			NA			kg	
Resistance to impact (method A)			NA			mm	
Watertightness under 10 kPa			Conforme			-	
Resistance to root penetration			NA			-	
Resistance to external fire exposure			FRoot (Note 1)			-	
Reaction to fire			NPD			-	
Dangerous substances			Note 2 and 3			-	

NA: not applicable due to use of product.

Note 1 : As the resistance to external fire exposure of roof depends on the complete system, no performance can be declared for the product alone.

Note 2 : This product does not contain asbestos or tar constituents

Note 3 : In the absence of European harmonized test methods, verification and declaration on release/content has to be done taking into account national provisions in the place of use.

The performances of the product identified above are in conformity with the declared performances.

In accordance with Regulation (UE)n°305/2011 , this declaration of performance is issued under the sole responsibility of the manufacturer identified above

Signed for and on behalf of the manufacturer by:
Peter Fleischmann (Managing Director)Paris
09/02/2024
