

IMPORTANT NOTE : Generally, not fully bonded upstand exceeding 500mm must be intermediate mechanically fixed according Archityne installation instructions.

— = denotes welding joint

RENOLIT ALKORPLAN F
membrane

RENOLIT ALKORMETAL
upstand trim

RENOLIT ALKORPLAN A
membrane

RENOLIT ALKORPLUS
81068/81168 PU adhesive.

RENOLIT ALKORPLAN D
cover strip

high point

min
50

RENOLIT
ALKORMETAL
upstand trim

Archityne
approved
fastener

RENOLIT ALKORPLAN A
membrane to base of gutter

NOTE: RENOLIT ALKORPLAN D
cover strips only required if
RENOLIT ALKORPLAN A is used
and not if F is used.

— = denotes welding joint

RENOLIT ALKORPLAN F
membrane fully bonded with
appropriate adhesive

min 300

high point

min
50

RENOLIT ALKORPLAN A
membrane

RENOLIT ALKORPLUS
81068/81168 PU adhesive.

RENOLIT ALKORPLUS peel
stop bar and fastener.

ALTERNATE VERSION
WITH PEEL STOP BAR.

— = denotes welding joint

RENOLIT ALKORPLAN F
membrane fully bonded with
appropriate adhesive

min 300

high point

min
50

RENOLIT ALKORPLAN D
cover strip

RENOLIT ALKORPLAN A
membrane

RENOLIT ALKORPLUS
81068/81168 PU adhesive.

NOTE: Gutter membrane
may be in one piece if it is
practical for installation

ALTERNATE VERSION
FULLY BONDED.

DO NOT SCALE

Notes

NOTE: All gutters to be sized
to suit the requirements on
NZBC E1 for each particular
roof catchment area

CodeMark

CMNZ70216

REV.	DATE	DESCRIPTION
1.	May 2026	First Issue

Archityne

Archityne Limited
PO Box 58129
Botany, Auckland
2163
New Zealand

TITLE:
RENOLIT ALKORPLAN A Perimeter
Box Gutter - Cold Roof On Concrete
Substrate.

SCALE	DATE	DRG NO.	REV. NO.
1:5@A3.	18/05/26	513	1.