

RENOLIT ALKORMETAL
drip edge trim.
—NOTE: Galvanised cleat
required when drip face is
over 100mm. Cleats to be
at 1mtr centres.

RENOLIT ALKORPLUS
—PES fleece 300 g/m²

 = denotes welding joint

Archityne
approved
fastener

RENOLIT ALKORPLAN D
—cover strip

RENOLIT ALKORPLUS
81068/81168 PU adhesive.

—Insulation

—Archityne
approved fastener

RENOLIT ALKORPLUS
—81002 self adhesive vapour
control layer

 = denotes welding joint

—RENOLIT ALKORPLUS peel
stop bar and fastener.

Archityne
approved
fastener

RENOLIT ALKORPLUS
81002 self adhesive —
vapour control layer

ALTERNATE VERSION
WITH PEEL STOP BAR.

 = denotes welding joint

RENOLIT ALKORPLUS —
81068/81168 PU adhesive.

RENOLIT ALKORPLUS
81002 self adhesive—
vapour control layer

ALTERNATE VERSION
FULLY BONDED UPSTAND.

DO NOT SCALE

Notes

CodeMark

CMNZ70216

REV.	DATE	DESCRIPTION
1.	May 2026	First Issue

Archityne

Archityne Limited
PO Box 58129
Botany, Auckland
2163
New Zealand

TITLE:
RENOLIT ALKORPLAN A Parapet
Encapsulation Detail With Drip Edge - Warm
Roof On Ply / Strandsarking Substrate

SCALE	DATE:	DRG NO.	REV. NO.
1:5@A3.	18/05/26	004	1.