

RENOLIT ALKORMETAL
drip edge trim.
—NOTE: Galvanised cleat
required when drip face is
over 100mm. Cleats to be
at 1mtr centres.

RENOLIT ALKORPLUS
—PES fleece 300 g/m²

IMPORTANT NOTE : Generally, not fully bonded upstand exceeding 500mm must be intermediate mechanically fixed according Architype installation instructions.

 = denotes welding joint

Substrate,
'by others'

—RENOLIT ALKORMETAL
edge trim.

—RENOLIT ALKORPLAN F

Archityne
approved
fastener

RENOLIT RENOLIT
ALKORMETAL upstand trim

RENOLIT ALKORPLAN
F membrane

—Archityne approved insulation washer

—Insulation

Deck, 'by others'—

—RENOLIT ALKORPLUS
LDPE vapour control layer

—Archityne
approved fastener

—RENOLIT ALKORPLAN F
membrane

RENOLIT ALKORPLAN F-
membrane

—RENOLIT ALKORPLUS peel
stop bar and fastener.

Archityne approved
insulation washer

Deck, 'by others'—

RENOLIT ALKORPLUS—
LDPE vapour control layer

ALTERNATE VERSION
WITH PEEL STOP BAR.

 = denotes welding joint

- RENOLIT ALKORPLAN F
membrane fully bonded with
appropriate adhesive

RENOLIT ALKORPLAN F-
membrane

—RENOLIT ALKORPLUS peel
stop bar and fastener.

Archityne approved
insulation washer

Archityne
approved
fastener

Deck, 'by others'—

RENOLIT ALKORPLUS—
LDPE vapour control layer

ALTERNATE VERSION
FULLY BONDED UPSTAND.

DO NOT SCALE

Notes

CodeMark

CMNZ70216

REV.	DATE	DESCRIPTION
1.	May 2026	First Issue

Archityne

Archityne Limited
PO Box 58129
Botany, Auckland
2163
New Zealand

TITLE:
RENOLIT ALKORPLAN F Parapet
Encapsulation Detail With Drip Edge
With Metal Deck Substrate - Warm Roof.

SCALE	DATE:	DRG NO.	REV. N
1:5@A3.	18/05/26	304	1.