



FROM PLASTIC TO PURPOSE · ACOUSTIC PANEL

ACOUSTIC PANEL

• 3 mm

FELTBAY Acoustic Panel.

SERIES

PET Felt Panel

MATERIAL

100% Polyester Fiber

RECYCLED CONTENT

≥ 80% Post-consumer



— INTRODUCTION

Acoustic panels, built with purpose.

FELTBAY Acoustic Panels are versatile sound-absorbing solutions designed for a wide range of interior applications. Lightweight, semi-rigid and engineered from **100% polyester fibre**, they balance acoustic performance with a refined, tactile finish.

Available in thicknesses from 5 mm to 24 mm, panels can be fully customised through printing, moulding, pressing, precision cutting, grooving and peel-and-stick application — and require no edging or capping for clean, seamless installation.

AT A GLANCE

THICKNESS 3 mm	DENSITY 600 g/m²
COMPOSITION 100% PET (≥80% rec.)	NRC (DIRECT) 0.10
FIRE CLASS ASTM E84 – Class A EN13501 – B-s1,d0*	

3 mm NOMINAL THICKNESS	0.10 NRC · DIRECT FIX	≥ 80 % RECYCLED PET
-------------------------------------	------------------------------------	-------------------------------

CUSTOMISATION

Printing · Moulding & Pressing · Precision Cutting · Grooving · Peel-and-Stick. No edging required.

APPLICATIONS

Wall lining · Ceiling panels · Acoustic features · Custom solutions.

**Majority of colours and range available to this standard, some colour/ranges achieve B-s2,d0.*

— SUSTAINABILITY

From plastic to purpose.

FELTBAY panels are engineered with a strong commitment to **sustainability**, **circularity** and **healthy indoor environments** — designed to meet international standards for environmental performance and material safety.

SUSTAINABILITY PILLARS

Recycled content · Low emissions · Circular design ·
Healthy interiors · Long lifecycle.



RECYCLED CONTENT

Manufactured from high levels of recycled PET — primarily post-consumer plastic bottles — reducing environmental impact and supporting a circular material economy.



INDOOR AIR QUALITY

Low VOC emissions contribute to improved indoor air quality and healthier interior spaces.



CIRCULAR DESIGN

Designed for a long lifecycle, reuse and recycling. Lightweight construction reduces transport emissions and overall environmental footprint.



GREEN BUILDING CONTRIBUTION

Feltbay panels contribute to LEED®, WELL, BREEAM and ESTIDAMA certifications through recycled content, low emissions and acoustic performance.

CERTIFICATIONS & COMPLIANCE



— SPECIFICATIONS

Product information & performance.

PRODUCT INFORMATION

PRODUCT NAME	FELTBAY PET Felt Panel — 3 mm
DESCRIPTION	Acoustic panel manufactured from thermally bonded high-density polyester fibres, for wall and ceiling applications.
COMPOSITION	100% polyester fibre (PET) . ≥ 80% recycled content
THICKNESS	3 mm (0.12" nominal)
DENSITY	600 g/m ² (≈ 1.8 oz/ft ²)
PANEL DIMENSIONS	1250 × 2800 mm (48.2" × 110.2") 1250 × 2440 mm (48.2" × 96.1")
TOLERANCE	± 5 mm (± 0.2")
MATERIAL CHARACTERISTICS	Non-woven PET panel · directional fibre grain · no pattern repeat · natural batch variation may occur.
INSTALLATION	Adhesive fixing · Mechanical fixing · Z-clip systems Install as per Feltbay guidelines.
APPLICATION	Wall lining · Ceiling panels · Acoustic features & custom solutions.

PERFORMANCE & TESTING

FIRE PERFORMANCE	ASTM E84 — Class A EN 13501-1 — B-s1,d0 / B-s2,d0
ACOUSTIC PERFORMANCE	3 mm (direct fix): NRC 0.10 50 mm air gap: NRC 0.50 50 mm air gap + insulation: NRC 0.90
MOISTURE PERFORMANCE	ASTM C1104 / C1104M 49 °C · 95% RH · 4 days — 0.4% by weight
IMPACT RESISTANCE	ISO 7892:1988 Hard body — no damage up to 9 J (0.5 kg / 2 m) Soft body — no damage up to 70 J (50 kg / 150 mm)
MICROBIAL RESISTANCE	ASTM G21 — Growth rating 0 (no growth)
COLOUR FASTNESS — LIGHT	ISO 105-B02:2014 — Rating 6 (scale up to 7)
COLOUR FASTNESS — RUBBING	ISO 105-X12:2016 — Dry 4–5 · Wet 4–5
MAINTENANCE	Clean with damp cloth. Upholstery shampoo if required. Avoid excessive water or abrasion.

— ACOUSTIC PERFORMANCE

Sound absorption, across the spectrum.

FELTBAY PET Felt panels provide high-performance sound absorption across a wide frequency range, enhancing acoustic comfort in interior environments. Tested in accordance with **EN ISO 354**.



PERFORMANCE HIGHLIGHTS

- Excellent mid- and high-frequency absorption
- Enhanced low-frequency performance with cavity or insulation
- Flexible performance depending on installation method
- Suitable for wall and ceiling applications

TEST METHOD

EN ISO 354 — Measurement of sound absorption in a reverberation room. Measurements conducted using pink noise as the excitation signal in a controlled reverberant environment.

— COLOUR OVERVIEW

Colours & light reflectance.

FELTBAY panels are presented in a carefully curated colour palette structured across **five distinctive collections** — supporting diverse architectural visions, from calm and minimal interiors to bold expressive spaces.

All colours are referenced to the **NCS (Natural Colour System)** for precise specification, with measured **Light Reflectance Values (LRV)** to support lighting design. Reflectance ρ represents the percentage of visible light reflected by the panel surface.

HOW TO READ


Colour name

S 2040-B10G

LRV 45

Each swatch shows the FeltBay theme name, the closest matching NCS code and the measured LRV value.

COASTAL

7 COLOURS · **NCS REFERENCE**

Inspired by sea and shore — cool blues, deep teals and bright tonal pairings to bring calm and depth to a space.


Alya

S 5010-B30G

LRV 25

Hawa

S 2020-B10G

LRV 50

Reef

S 7020-B10G

LRV 8

Laz

S 4550-R80B

LRV 11

Dana

S 2040-B10G

LRV 45

Sama

S 2030-R90B

LRV 49

Nyla

S 8505-R80B

LRV 4

STONE

9 COLOURS · **NCS REFERENCE**

A foundation of warm and cool neutrals — calm, architectural and timeless.


Sora

S 1002-Y80R

LRV 75

Niva

S 1002-G

LRV 79

Sia

S 9000-N

LRV 3

Lina

S 6000-N

LRV 26

Dujan

S 7502-G

LRV 14

Zill

S 8502-G

LRV 9

Rimah

S 3000-N

LRV 53

Marmar

S 3502-Y20R

LRV 47

Fidda

S 2502-Y50R

LRV 55

— COLOUR OVERVIEW · CONTINUED

Desert & Forest.

DESERT

11 COLOURS · NCS REFERENCE

Sun-baked ochres and earth tones — warmth, grounding and the patina of arid landscapes.

	Dune S 5010-Y10R LRV 34		Sahara S 3010-Y10R LRV 53		Cedar S 6020-Y40R LRV 18		Masa S 2502-Y LRV 59
	Ziya S 2040-Y10R LRV 48		Savannah S 3050-Y80R LRV 27		Date S 8010-Y50R LRV 10		Nour S 3010-Y60R LRV 48
	Ivra S 2005-Y40R LRV 60		Terra S 3050-Y50R LRV 30		Wadi S 4050-Y60R LRV 20		

FOREST

8 COLOURS · NCS REFERENCE

Living greens — from yellowed grasses to deep canopy. Biophilic palettes for restorative spaces.

	Tala S 7020-G50Y LRV 12		Nael S 5030-G30Y LRV 23		Zena S 3005-G50Y LRV 52		Maha S 4010-G70Y LRV 62
	Layan S 7020-Y LRV 13		Rayan S 3060-G70Y LRV 34		Lura S 8505-G LRV 5		Asel S 1080-G30Y LRV 43

— COLOUR OVERVIEW · CONTINUED

Vibrant accents.

VIBRANT

6 COLOURS · NCS REFERENCE

Saturated highlights — energetic accents for moments of contrast and focus.



Nari
S 2070-Y50R
LRV 31



Aven
S 7020-Y90R
LRV 5



Amara
S 2570-R
LRV 13



Lulu
S 3010-R50B
LRV 47



Auri
S 0560-G90Y
LRV 73



Rubi
S 2570-R
LRV 10

COLOUR INFORMATION & DISCLAIMER

NCS Colour Matching — The indicated NCS colour codes represent the closest visual reference and may not be an exact match due to the natural blending of fibres.

Recommendation — It is recommended to request a sample set to verify colours prior to specification or installation. Slight variations in reflectance may occur due to the natural composition of PET fibres and the textured surface of the material — these nuances contribute to the product's authentic finish.

— GET IN TOUCH

Made in the UAE. Enhancing spaces worldwide

For technical specifications, sampling, or custom-fabrication enquiries —
please contact your FELTBAY account manager or reach out below.

WEBSITE

feltbay.com

ENQUIRIES

info@feltbay.com

HEAD OFFICE

Abu Dhabi, United Arab Emirates

DOCUMENT

Technical Data Sheet · 3 mm

