

Assembly and Installation of the BLACK X xPad+

Tools Required

- Phillips head screwdriver
- Keypad ejector tool (included)

Note: Keep the keypad ejector tool for future battery replacements.

1 Unbox and Prepare Components

Open the package and identify all components. Lay them out for easy access.

The package includes:

- | | |
|-------------------------|-------------------|
| 1 x xPad+ | 2 x Screws |
| 1 x 3M adhesive pad | 4 x AAA Batteries |
| 1 x Keypad ejector tool | 2 x NFC cards |



2 Remove the Back Cover of the xPad+

Using the Keypad ejector tool, remove the back cover of the xPad+ by inserting the pin into the designated hole at the bottom of the device.




3 Place the Batteries

1. Open the battery compartment cover.
2. Insert the batteries, ensuring they are correctly positioned. The xPad+ will power on and emit a beep to confirm proper installation.



4 Pair the xPad+ with the BLACK X app

1. Open the BLACK X App, navigate to the lock you wish to pair with the xPad+, and tap the Settings button .
2. In the Settings menu, select xPad/xPad+, then tap "xPad+", touch the xPad+ to activate and click "continue" keypad".
3. If your xPad+ appears in the list of available devices, select it to complete the pairing process. If it doesn't appear, locate the Pairing Key in the small hole just above the battery compartment on the xPad+. Use the Keypad ejector tool to press the button inside. The xPad+ will begin flashing to indicate pairing mode, then select it from the list to complete the process.
4. Close the battery compartment cover securely.



5 Secure the xPad+ to the Surface

Choose a suitable location for installing the xPad+. Ensure it is within 10 feet (3 meters) of the lock for standard doors. For best performance, especially for steel doors, it is strongly recommended to place the xPad+ as close as possible to the door and lock to maintain the strongest Bluetooth connection.




Option 1

1. Use the two screws and a Phillips head screwdriver.
2. Position the back cover of the xPad+ on the surface and secure it by inserting the screws into the two designated holes.
3. Slide the xPad+ into the back cover and ensure it is securely in place.

Option 2


1. Peel off the backing from one side of the 3M adhesive pad.
2. Carefully place the adhesive pad on the back cover of the xPad+, ensuring proper alignment.
3. Peel off the backing from the other side of the adhesive pad.
4. Stick the back cover of the xPad+ to the chosen position on the surface.
5. Slide the xPad+ into the back cover and ensure it is securely in place.




6 Set Up Unlocking Methods and Test Functionality

Unlock your door with the BLACK X xPad+ using one of the following methods: passcode, fingerprint, or NFC for seamless entry.

To configure the unlocking methods:

1. Open the BLACK X app on your smartphone.
2. Navigate to the main menu  and choose your desired unlocking option (passcode, fingerprint, or NFC) and follow the prompts in the app.
3. Once configuration is complete, test the selected unlocking method with the BLACK X smart lock.



Note: Ensure you follow the on-screen instructions carefully for a successful setup.

Examples of unlocking methods



Passcode entry



Fingerprint scan



NFC card



NFC tag


The xPad+ is supplied with 2 NFC cards.
Additional NFC cards or tags can be purchased separately to suit your operational needs.

7 Online Instructions

Need help with installation
or have questions?



www.black.inc



XPP-EN