

TM 150E2 Solderable Conductive Adhesive Product Datasheet

Enhance Reliability
Improve thermal conductivity
Eliminate outgassing

Description

TM 150E2 solderable conductive adhesives are designed for both solderable surface application which can be used as die attach adhesives for LED, CSP, QFP, and thermal interface materials, particularly for bare die and heat spreader, to replace conductive adhesives (Ag) or solder materials such as solder paste or preform. By comparison with conductive adhesives (Ag), TM 150E2 solderable adhesives have higher stable electrical and thermal conductivity, are able to easily fill-gap and self-level die, and easily control the bonding thickness. By comparison with soldering materials, TM 150E2 solderable adhesives eliminate the outgassing from soldering process, die skewing, shifting, and soldering bleed. The soldered interface will be encapsulated with the curing of TM 150E2 solderable adhesives, thus the soldered metal interface is protected by a 3D polymer network, which can tolerate harsh environmental conditions.

Typical Physical Properties

Product Name	TM 150E2 solderable adhesives
PROPERTIES OF UNCURED MATERIAL	
Filler	Silver
Resin Type	Epoxy
Specific Gravity (ASTM D 1475-60)	3.5 – 4.5 g/cc
Viscosity (Brookfield, 0.5 rpm)	50 – 100 kcp

PROPERTIES OF CURED MATERIAL	
Tensile Strength (MPa)	56
C.T. E (ASTM E 831), PPM /°C	23.5
Young's modulus (GPa)	26.3
Thermal conductivity (W/mK)	60 – 90
Extractable ions (MIL-STD-883E)	
Na+	<5ppm
K+	<5ppm
F-	<5ppm
Cl-	<10ppm

Recommended Curing Conditions

Use industrial standard low temperature lead free reflow (165 – 170°C Peak Temperature)

Storage & Shelf Life

6 months provided materials are kept in a sealed original container at – 40°C. Storage beyond this period can produce higher viscosity. Protect from moisture, evaporation and foreign materials. Process ability of these products can be adversely affected by evaporation and contamination.

Safety

TM150E2 is a friendly, non-toxic material. However, general hygiene practice is recommended when handling this material. For detailed information please consult our SDS.

Package

TM 150E2 solder adhesives are available in 10cc and 30cc. Other packages are available depending upon customer's request. Contact YINCAE for order information.