

QUIVOGNE

3 to 12 m



Image: HET hydraulically foldable

HET

RIGID

HYDR. FOLDABLE

LIGHT WEEDER HARROW / 6 ROWS / MOUNTED

PRODUCT FEATURES

- Working width 3 – 12 m
- For tractors 40 – 130 HP
- Frame profile 100 x 100 mm
- Adjustable tine angle (6 positions)
- Tine sections with pendular mounting and draw chains
- Transport width 3 m

STANDARD FEATURES

- Three-point linkage Cat. 2
- Angled tines Ø 7 mm / length 480 mm
- 2 – 8 tine sections with 6 tine rows
- Up to HET 900: 1 hydraulic folding cylinder
- HET 900 R – 1200 R: 2 hydraulic folding cylinders
- HET 300 – 600: 2-wheel-chassis with tyres 16x6.50x8
- HET 750 – 1200: 4-wheel-chassis with tyres 18x7x8
- Stand

OPTIONS

- Tines Ø 8 mm
- Levelling board
- Additional wheels for HET 450 and 600
- Warning plates and lighting

FIELD OF APPLICATION / ADVANTAGES

- The mounted weeder harrow HET was designed for eco-friendly weed control – the use of herbicides can be therefore reduced.
- Up to 8 tine sections with up to 432 tines (angled for careful soil cultivation) allow an intensive loosening of the soil surface.
- The pendular mounting of the tine sections ensures an optimal adaption to the soil contour during the workflow.
- Recommended working speed: 20 km/h



Tine sections with angled tines



Tine angle adjustment

HET: with 6 tine rows, tines Ø 7 mm / length 480 mm

RIGID


Model	Article Code	Working width (cm)	Tine sections	Tines (pcs.)	Weight (kg)	Required power (HP)
HET 300	M 1260 010	300	2	108	330	40 - 60
HET 450	M 1260 011	450	3	162	470	50 - 70
HET 600	M 1260 012	600	4	216	650	60 - 80
HET 750	M 1260 013	750	5	270	750	70 - 90
HET 900	M 1260 014	900	6	324	930	80 - 100

HET: with 6 tine rows, tines Ø 7 mm / length 480 mm

HYDR. FOLDABLE

Model	Article Code	Working width (cm)	Tine sections	Tines (pcs.)	Weight (kg)	Required power (HP)
HET 900 H	M 1260 020	900	6	324	1.580	80 - 100
HET 1050 H	M 1260 021	1050	7	378	1.690	90 - 120
HET 1200 H	M 1260 022	1200	8	432	1.800	110 - 130

OPTIONS FOR HET

	Article Code	Weight (kg)
Tine Ø 8 mm <i>instead of Ø 7 mm</i>	E 1260 500	
Levelling board (<i>per tine section</i>)	E 1260 501	10
Additional wheels for HET 450 and 600 <i>with fasteners</i>	E 1260 502	25
 Warning plates and lighting (<i>1 pair</i>)	E 1260 503	12



HET hydraulically foldable, chassis, stand



HET transport position

Note: For the operation of the weeder harrow HET hydraulically foldable the tractor has to be equipped with 1 double-acting unit.

QUIV OGNE